

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
DOME PETROLEUM CORP.
3. ADDRESS OF OPERATOR 501 Airport Drive,
Suite 114, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17
below.)
AT SURFACE: 820' FNL, 1830' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Spud & Set Surface Casing		

5. LEASE
N00-C-14-20-5051
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
DOME NAVAJO 34-22-6
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Rusty Chacra Extension
11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA
Sec. 34, T22N, R6W
12. COUNTY OR PARISH
Sandoval
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7044' GR

(NOTE: Report results of multiple completion or zone
change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12½" hole at 11:30 p.m., 12/07/80. Drilled to 145'. Ran
3 jts. (137') 8 5/8", 24#, K55, R-3, ST&C Casing. Casing landed
at 138' G.L. Cemented with 100 sxs. Class "B" Cement with 2% CaCl.
Plug down at 5:00 a.m., 12/08/80. Circulated cement.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. HOLLINGSWORTH TITLE Drilg. & Prod. Foreman DATE Dec. 8, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

MOCC

*See Instructions on Reverse Side

BW

