

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

THIS REPORT IS TO BE COMPLETED FOR ALL WELLS OR TO REPORT ON A WELL TO A DIFFERENT REGION OR DISTRICT FOR THE PURPOSES OF THIS FORM.

1. Well Casing Other

2. NAME OF OPERATOR
DOME FEDERAL OIL CO.

3. ADDRESS OF OPERATOR
571 Airport Drive,
Suite 110, Farmington, New Mexico 87401

4. LOCATION OF WELL REPORT LOCATION (SEE FIG. See space 17 below)
AT SURFACE 10° 15' N, 86° 15' W
AT TOP PROD. INTERVAL
AT TOTAL DEPTH

5. LEASE
NW 6681

6. IF INDIAN ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Dome Federal 10-22-7

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Rusty Chacra Extension

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 10, T20N, R7W

12. COUNTY OR PARISH 13. STATE
Sandoval New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6983' CR

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
REVISION <input type="checkbox"/>	<input type="checkbox"/>
Other <input type="checkbox"/> Spud / Set Surface Casing	

RECEIVED
SEP 15 1980
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 12 1/2" hole at 1:00 p.m. 9/10/80. Drilled to 136'. Ran 3 jts. (134') 1 1/2" 14# P53, ST&C Casing. Casing landed at 134' G.L. Cemented with 100 sacks Class 'F' Cement with 2% CaCl. Plug down at 9:00 p.m. 9/10/80. Circulated cement.

SEP 18 1980
OIL CON. COM.
DIST. 3

Subsurface Safety Valve Model and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

By [Signature] TITLE Regional District Foreman DATE September 11, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
ACCEPTED FOR RECORD IF ANY:

SEP 15 1980

NMOCC

*See Instructions on Reverse Side

BY DW
FARMINGTON DISTRICT