UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	NM24141 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
deological Survey	E A S O S S S S S S S S S S S S S S S S S
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME 2 9 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME G
1. oil gas K other	Alamos Canyon 2 5 5 5 5 9. WELL NO. 5 5 5 5 5 5
2. NAME OF OPERATOR Jack A. Cole	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Wildcat
P. O. Box 191, Farmington, N.M. 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 6-T21N-R6W
AT SURFACE: 1010/S & E Sec. 6-T21N-R6W AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH 13. STATE Sandoval See New Mexico
AT TOTAL DEPTH: Same	14. API NO. = 15.5.0
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	PÜEL E EERE
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6782 Gr.
TEST WATER SHUT-OFF	6
FRACTURE TREAT	(NOTE: Report results of multiple completion przehe change on form 9-350)
REPAIR WELL	(NOTE: Report results of martingle completion przobe
PULL OR ALTER CASING OCT 27	1080 change on form 9-330)
CHANGE ZONES U. S. GEOLOGICA	
ABANDON* (other) Running Casing FARMINGTON,	N. M.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
8-20-80 Spud well. Ran 3 joints 8 5/8",	24.0 casing to 134' 6 Cemented
with 135 sacks. Cement circulated. WOC	24 hours. 28-28-80 Reached TD
1497'. Attempt to log, hole caving in, logs would not go. Ran 39 joints	
4½" casing to 1485'. Cemented with 195 s	sacks 50:50 poz-2% get, 6 lbs.
salt per sack. Cement circulated. 10-6-	-80 MICT. Drilled cement
1284 to 1387. 10-8-80 Ran Schlumberger 5 1343 with 29 holes. Sand water fraced with 29 holes.	IDT log to \$400: perra 1304-
tons CO2, 40,000 lbs. 20-40 sand. BDP 13	
well to pit to clean up after frac. 10-	
Landed at 1303'. Blew well to clean up it	그 그는 그 불자 하는 한 그 게 끝났다면
•	다 다 다 다 다 다 다 다 다 다 다 다 다 다 다 다 다 다 다
	One of the same of
•	the of guideout TP TP TP TP TP TP TP TP TP T
Subsurface Safety Valve: Manu. and Type	
18. I hereby certify that the foregoing is true and correct	24.01.2 2.02.0.0 2.00.0.0.0.0.0.0.0.0.0.0.0.0
() call // lake manatan	
SIGNED TITLE OPERATOR	DATE OCTOBER 24, 01880
(This space for Federal or State office use)	
APPROVED BY TITLE	こうしょう こうしゅう はっちょう はっちょう はんしゅう はんしゅう かんしゅう しゅうしゅう しゅう
CONDITIONS OF APPROVAL, IF ANY:	
	Find Sond Sond Sond Sond Sond Sond Sond So
	1 6 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

*See Instructions on Reverse Side

FALLUROTON, SHOUNCT