

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well    gas ☒ well    other

2. NAME OF OPERATOR

J. Gregory Merrion & Robert L. Bayless

3. ADDRESS OF OPERATOR

P. O. Box 507, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1650 FSL & 990 FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Drilling ☒

5. LEASE

Contract 163

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Badland Flats

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

So. Blanco Pic. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 24, T23N, R2W

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

14. API NO.


15. ELEVATIONS (SHOW DF, KDB, AND WD)

7336 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

See attached report.



Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. Gregory Merrion TITLE Co-Owner DATE November 17, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

**NMOCC**

\*See Instructions on Reverse Side

BW

MERRION & BAYLESS  
BADLAND FLATS #1  
1650 FSL & 990 FWL  
Section 24, T23N, R2W  
Sandoval County, N.M.

DAILY REPORT

- 11-7-80 Moved in, rigged up James Drilling Co. Spudded 9-3/4" hole and set 96 ft. of 7", 23 lbs/ft, J-55 surface casing with 50 sacks. WOC.
- 11-8-80 Drilling at 1250. Water loss 8.0; weight 8.7; viscosity 32.
- 11-9-80 Drilling at 2325.
- 11-10-80 Lost cone and fished out; going back in @ 2725.
- 11-11-80 Reached TD at 3125 ft. Now running logs.
- 11-12-80 Rig up Birdwell. Ran Induction log TD to surface casing. Ran Density log TD to 1700 ft. Ran in hole. Circulated 30 minutes and laid down drill pipe. Prepared to run casing. Ran 3103' 2-7/8", blue band, J-55 used casing. Baffle @ 3071'. Set @ 3107 K.B. Cemented w/ 225 sx Class B 2% D-79 and 50 sx Class H 2% gel. Displaced w/ 250 gal. acetic acid and 12 bbls sugar water. Circulated cement back to surface. Plug latched in @ 5:30 p.m. (JCA)