UNITED STATES	Budget Bureau No. 42-R1424		
	5. LEASE		
DEPARTMENT OF THE INTERIOR	NOO/- C - 14 - 20 - 5829		
GEOLOGICAL SURVE	6. IF INDÍAN, ALLOTTEE OR TRIBE NAME Navajo		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deed for plug back to addrerent reservoir. Use Form 9-331-C for such proposals.) 1. oil gas gas	7. UNIT AGREEMENT NAME		
SUNDRY NOTICES AND REPORTS ON SPELLS (Do not use this form for proposals to drill or to deed for plug back to offerent reservoir. Use Form 9-331-C for such proposals.) 1. oil gas well other 2. NAME OF OPERATOR Lewis Energy Corporation	8. FARM OR LEASE NAME Lopez		
2. NAME OF OPERATOR	9. WELL NO. No. 1		
3. ADDRESS OF OPERATOR	Wildcat		
1801 Broadway, Ste 1600 Denver, CO 80202 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA		
below.) AT SURFACE: 990' FWL & 990' FSL FSL Sec.8	Sec. 8, T20N R4W, NMPM		
AT TOP PROD. INTERVAL: Same as above	1 SOUTH ON TAKISH 13. STATE		
AT TOTAL DEPTH: Same as above	Sandoval New Mexico		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.		
REPORT, OR OTHER DATA	15 5151/471011		
, ma	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6834' GR 6844' KB		
REQUEST FOR APPROVAL TO: SUBSEQUEST REPORT OF:	0034 dit (0044 KB		
TEST WATER SHUT-OFF	and the second of the second o		
SHOOT OR ACIDIZE	may a series of the series of		
REPAIR WELL	(NOTE: David		
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone		
MULTIPLE COMPLETE	1.65 (30)		
	og Jal Survey		
(other) Progress Report	270N, N. W.		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers; and zones pertinent	e all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and		
Using cable tools, drilled out of 7" casing s	set at 3836'. Encountered water		
TOW & JOHL WING COULD HILL HITLI AND READER	D/II calbo toola niiion i		
Power Swiver. Fillighed drift to 111 4x00, by	n loge. Dil/Con co .		
set $4\frac{1}{2}$ " liner from 3668' - 4800". Cemented w	1/55 sx 50/50 Pos. Perforated		

4030'-4080' w/2 spf. Acidized perfs w/2000 gal 15% HCl. Swab back acid and load water. Swab tested 120 bbls water in 10 hours. SI well and released completion unit. Temporarily Abandoned ---- pending further evaluation.

Subsurface Safety Valve: Manu. and Type		Set @		Ft.
18. I hereby certify that the foregoing				
SIGNED PLEASURE NAME	TITLE VP Operations	DATE	-scano	
	(This space for Federal or State office use)	DATE ACCEPTED	LON HERE	
APPROVED BY	TITLE	DATE ACCEPTED	1982	
SOMETHORS OF AFFROYAL, IF ANY:		In	4 13 ON DISTRICT	
	*See Instructions on Reverse Side	FARM	Moro	-

NMOCC