

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
DOME PETROLEUM CORP.

3. ADDRESS OF OPERATOR 501 Airport Drive,
Suite 114, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 830' FNL, 790' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Set Production Casing

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

N00-C-14-20-5365

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dome Tesoro #27

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Undesignated Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 27, T22N, R7W

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6781' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 126 jts. (4995') 4½", 10.5#, K55, ST&C Casing. Casing landed at 4997' K.B. Cemented 1st stage with 300 sx. 65/35 Pozmix, 6% Gel, and 10# Gilsonite/sx. Followed with 200 sx. Class "B" Cement with 10% salt. Plug down at 8:15 a.m., 1/20/81. Opened DV Tool and circulated 4 hrs. Cemented 2nd stage w/250 sx. 65/35 Pozmix, 6% Gel, & 10# Gilsonite/sx. Followed with 300 sx. Class "B" Cement with 10% salt. Plug down at 1:30 p.m., 1/20/81. Circulated cement on both stages.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. HOLINGSWORTH TITLE Drlg. & Prod. Foreman DATE Jan. 21, 1981

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

JAN 27 1981

*See Instructions on Reverse Side