completed.

5. LEASE

NM 12812

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| AREA Sec. 34, T18N R3W AT SURFACE: 976' FNL 385' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND Note) 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 16. ELEVATIONS (SHOW DF, KDB, AND Note) 6480' GR (NOTE: Report results of multiple completion or a change on Form 9-330.) (NOTE: Report results of multiple completion or a change on Form 9-330.) TO ESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations a measured and true vertical depths for all markers and zones pertinent to this work.)* | GEOLOGICAL SURVEY | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
|--|--|--|
| 1. oil | SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a difference than Form 9, 221 Colorado and the control of the form 10, 221 Colorado and the control of the form 10, 221 Colorado and the control of the | 7. UNIT AGREEMENT NAME |
| NOTE REPORT CASING MULTIPLE COMPLETE CO | Testivon, Use Form 9-331-C for such proposals.) | 8. FARM OR LEASE NAME |
| 2. NAME OF OPERATOR RUTH ROSS 3. ADDRESS OF DEPRATOR P. O. BOX 464, SANTA FE, NM 87501 4. COCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 976' FNL 385' FNL AT TOP PROD. INTERNAL: AT TOTAL DEPTH: | | South San Luis |
| RUTH ROSS 3. ADDRESS OF OPERATOR P. O. BOX 464, SANTA FE, NM 87501 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below). AT SURFACE: 976' FNL 385' FWL AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND V 6480' GR 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dameasured and true vertical depths for all markers and zones pertinent to this work.) This well has been plugged with 50 sacks of Portland cement as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface locations. The work was completed September 10, 1982. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type Chiis space for Foderal or State office use) Chiis space for Foderal or State office use) APPROVED BY Well bore. OCT 24 1984 | | 9. WELL NO. |
| 3. ADDRESS OF OPERATOR P. O. BOX 464, SANTA FE, NM 87501 A LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 976' FNL 385' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON'. Plugging. Completed 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent damesured and true vertical depths for all markers and zones pertinent to this work.)* This well has been plugged with 50 sacks of Portland Cement as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface 18 of the proposed March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface 18 of the proposed March 31, 1982, by placing a 100' cement plug from 255' to 325' and a 100' plug from a depth of 100' to the surface 18 of the proposed March 31, 1982, by placing a 100' cement plug from 255' to 325' and a 100' plug from a depth of 100' to the surface 18 of the proposed March 31, 1982, by placing a 100' cement plug from 255' to 325' and a 100' plug from a depth of 100' to the surface 18 of the proposed March 31, 1982, by placing a 100' cement plug from 255' to 325' and a 100' plug from a depth of 100' to the Surface 18 of the proposed March 31, 1982, by placing a 100' cement plug from 255' to 325' and a 100' plug from a depth of 100' to the Surface 18 of the proposed March 31, 1982, by placing a 100' cement plug from 325' to 325' and a 100' plug from 325' to 325' and 300' plugging of the 325' plugging of | | 42 |
| P. O. BOX 464, SANTA FE, NM 87501 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 ALLOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AREA SEC. T. R., M., OR BLK. AND SURVEY AREA SURVEY. SURVEY. SURVEY. SURVEY. SEE SPACE 17 AREA SEC. T. R., M., OR BLK. AND SURVEY. AREA SURVEY. SEE SPACE 17 AREA SEC. T. R., M., OR BLK. AND SURVEY. AREA SURVEY. AR | RUTH ROSS | 10. FIELD OR WILDCAT NAME |
| A LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 976' FNL 385' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 16. THE WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES ABANDON' (Other) Plugging Completed 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent as measured and true vertical depths for all markers and zones pertinent to this work.) This well has been plugged with 50 sacks of Portland cement as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface and the vertical depths for all markers and zones pertinent to this work.) Subsurface Safety Valve: Manu. and Type 18. I herebypartify that the foregoing is true and correct SIGNED The work was completed September 10, 1982. (This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL IF ARY. DATE APPROVEL AS AMEND. APPROVED BY CONDITIONS OF APPROVAL IF ARY. DATE APPROVEL AS AMEND. APPROVED BY CONDITIONS OF APPROVAL IF ARY. DETAIL BEFORE TO THE AS A SAMEND. APPROVED BY CONDITIONS OF APPROVAL IF ARY. DETAIL BEFORE THE SEE SEE SEED TO THE AS AMEND. APPROVED BY CONDITIONS OF APPROVAL IF ARY. DATE AS AMEND. | | South San Luis |
| AT SURFACE: 976' FNL 385' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 17. DESCRIBE FOR APPROVAL TO: SUBSEQUENT REPORT OF: SET WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) Plugging Completed 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dameasured and true vertical depths for all markers and zones pertinent to this work.)* This well has been plugged with 50 sacks of Portland cement as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface. The work was completed September 10, 1982. (This space for Federal or State Office use) (This space for Federal or State Office use) APPROVED APPROVED BY CONDITIONS OF APPROVAL IF ANY: DOTOLOGY OF A PROPOVAL IF ANY: DOTOLOG | 4. LOCATION OF WELL (REPORT LOCATION CLEARLY See space | 11. SEC., T., R., M., OR BLK. AND SURVEY C |
| AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE O(Gher) Plugging Completed 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent da measured and true vertical depths for all markers and zones pertinent to this work.)* This well has been plugged with 50 sacks of Portland cement as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface 18. The work was completed September 10, 1982. Subsurface Safety Valve: Manu. and Type 18. Thereby-pertify that the foregoing is true and correct signed by the state of the surface o | | Sec. 34, I18N R3W |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 15. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 15. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 16. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: 16. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 17. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 17. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 18. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 17. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 17. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 17. ELEVATIONS (SHOW DF, KDB, AND V 6480 ' GR 18. ELEVATION (SHOW) GR 18. ELEVATION (SHOW) GR 19. ELEVATION (SHOW) GR 19. ELEVATION (SHOW) GR 19. ELEVATION (SHOW) GR 19. ELEVA | AT TOP PROD. INTERVAL: | I I |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND N 6480' GR 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND N 6480' GR 16. CHECK APPROPOVAL TO: SUBSEQUENT REPORT OF: 16. ELEVATIONS (SHOW DF, KDB, AND N 6480' GR 16. CHECK APPROPOVAL TO: 16. ELEVATIONS (SHOW DF, KDB, AND N 6480' GR 16. CHECK APPROPOVAL TO: 16. ELEVATIONS (SHOW DF, KDB, AND N 6480' GR 16. ELEVATIONS (SHOW DF, KDB, AND N 6480' GR (NOTE: Report results of multiple completion or of the substance of the | AT TOTAL DEPTH: | - Sandoval New Mexico |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 1 | 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA | CE, |
| TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE SHOT OR ACIDIZE SHOOT | • | |
| Subsurface Safety Valve: Manu. and Type 18. I hereby pertify that the foregoing is true and correct Signed March Signed M | | L6480' GR |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)* This well has been plugged with 50 sacks of Portland cement as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface. The work was completed September 10, 1982. Subsurface Safety Valve: Manu. and Type Set @ 18. I hereby partify that the foregoing is true and correct signed with 50 sacks of Portland cement as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface. The work was completed September 10, 1982. Subsurface Safety Valve: Manu. and Type Set @ (This space for Federal or State office use) APPROVEI APPROVED AS AMENDED TO State of Portland Cement as a provided as to plugging of the well bore. | SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* HOLD ALTER CASING ABANDON* | (NOTE: Report results of multiple completion or zor change on Form 9–330.) |
| This well has been plugged with 50 sacks of Portland cement as approved March 31, 1982, by placing a 100' cement plug from 225' to 325' and a 100' plug from a depth of 100' to the surface. The work was completed September 10, 1982. Subsurface Safety Valve: Manu. and Type 18. I hereby partify that the foregoingn's true and correct signed the complete specific | | |
| Subsurface Safety Valve: Manu. and Type | This well has been plugged with 50 as approved March 31, 1982, by place | sacks of Portland cement |
| 18. I hereby, partify that the foregoing is true and correct SIGNED TITLE Agent DATE September 22, 1982 (This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY: proved as to plugging of the well bore. OCT 24 1984 | | The state of the s |
| 18. Thereby, certify that the foregoing is true and correct SIGNED TITLE Agent DATE September 22, 1982 (This space for Federal or State office use) APPROVED BY TITLE DATE AS AMEND DEPONDED TO September 22, 1982 CONDITIONS OF APPROVAL, IF ANY: Deponded as to plugging of the well bore. | | The state of the s |
| 18. Thereby, certify that the foregoing is true and correct SIGNED TITLE Agent DATE September 22, 1982 (This space for Federal or State office use) APPROVED BY TITLE DATE AS AMEND DEPONDED TO PROVED BY DATE AS AMEND DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DATE | | 23.7 |
| 18. Thereby, certify that the foregoing is true and correct SIGNED TITLE Agent DATE September 22, 1982 (This space for Federal or State office use) APPROVED BY TITLE DATE AS AMEND DEPONDED TO PROVED BY DATE AS AMEND DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DATE | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | CANAL DE CONTRACTOR |
| 18. Thereby, certify that the foregoing is true and correct SIGNED TITLE Agent DATE September 22, 1982 (This space for Federal or State office use) APPROVED BY TITLE DATE AS AMEND DEPONDED TO PROVED BY DATE AS AMEND DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DATE | g y Left filt of the control of the | 100 CO CONTRACTOR |
| 18. Thereby, certify that the foregoing is true and correct SIGNED TITLE Agent DATE September 22, 1982 (This space for Federal or State office use) APPROVED BY TITLE DATE AS AMEND DEPONDED TO PROVED BY DATE AS AMEND DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DATE | | Committee of the commit |
| 18. Thereby, certify that the foregoing is true and correct SIGNED TITLE Agent DATE September 22, 1982 (This space for Federal or State office use) APPROVED BY TITLE DATE AS AMEND DEPONDED TO PROVED BY DATE AS AMEND DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DEPONDED BY DEPONDED BY DATE DATE DATE DATE DATE DATE DATE DATE | Subsurface Safety Valve: Manu, and Type | |
| (This space for Federal or State office use) APPROVED APPROVAL, IF ANY: DATE OF APPROVAL, IF ANY: Or oved as to plugging of the well bore. OCT 24 1984 | 100 | Set @ F |
| (This space for Federal or State office use) APPROVED APPROVED CONDITIONS OF APPROVAL, IF ANY: DATE AS AMEND OCT 24 1984 Well bore. | 1/2 iv \(\Lambda \tau\) | DATE September 22 1082 |
| proved as to plugging of the well bore. TITLE TITLE DATE AS AMEND OCT 24 1984 | | |
| proved as to plugging of the well bore. TITLE TITLE DATE AS AMEND OCT 24 1984 | (Inis space for Federal or State | APPROVED |
| proved as to plugging of the well bore. OCT 24 1984 | APPROVED BY TITLE | |
| well bore. OCT 24 190 | | • - |
| hility under pond is relatived | well bore. | OCT 24 1984 |
| ntil surface restoration is Instructions on Payerra Side | bility under bond is relatived | the That |