

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Pelto Oil Company
3. ADDRESS OF OPERATOR Texas 77060
16825 No. Chase Dr., Suite 400, Houston
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980 FSL 990 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Set Surface Casing

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

JUN 22 1981

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion change on Form 9-331-C)

5. LEASE
NM26185
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Blackshare Federal
9. WELL NO.
No. 1
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
35-T14N-R6E
12. COUNTY OR PARISH
Sandoval
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6014 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Move in and rig up Loffland Rig No. 5. Spud 17½" surface hole at 0800 hrs., 6/14/81. Drilled to 560 ft. Ran 15 jts. 13 3/8", 54.5#, K-55 buttress casing and set at 532 ft. Rigged up Halliburton and cemented with 890 sacks Class "B" cement, 2% CaCl, 1/4# Flocele. Plug down 0640 hrs., 6/16/81. Circ. 40 sacks cement back to surface. WOC 8 1/2 hrs. Then 17 1/2 hrs. WOC, installing wellhead and nipping up BOP. Pressure tested casing and BOP for 30 minutes at 1000 psi at 2100 hrs., 6/17/81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark E. Wender TITLE Geological Consultant DATE 6/19/81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

NMOCC

BY

FARMINGTON DISTRICT

JUL 01 1981
Dean Elliott