

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

T.L. MORRIS

3. ADDRESS OF OPERATOR

P.O. BOX 1038 KILGORE, TEXAS 75662

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

2310 FSL 330 FEL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other) ☐

SUBSEQUENT REPORT OF

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

RECEIVED

JAN 4 1982

U. S. GEOLOGICAL SURVEY

Report results of multiple completion
change on Form 9-330

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/27/81 WE PROPOSE TO PLUG WELL WITH 50 FT. CEMENT PLUG
ON BOTTOM, ALSO SET 50 FT. CEMENT PLUG ON TOP.

Subsurface Safety Valve Model and Type

18. I hereby certify that the foregoing is true and correct.

Signed

Jim Pippa

TITLE AGENT

DATE 10/27/81

(This space for Federal or State office use)

APPROVED BY

POSITION AND SIGNATURE

TITLE

DATE

*See Instructions on Reverse Side

NMOCC

