16.

## UNITED STATES DEPARTMENT OF THE INTERIOR (Other in verse side) GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE.

Form approved.

NM-11928

	Budget	Burea	u No.	42-R	142
5. LEASE	DESIGN	ATION A	ND SI	RIAL	NO.

6. IF INDIAN, ALLOTTER OR TRIBE NAME

SUNDRY NO	OTICES AND	REPORTS	ON	WELLS
-----------	------------	---------	----	-------

	(Do not use this form	for proposal	s to drill or	to deepen or pl RMIT" for suc	ug back to a		r.				
1.	OIL GAS WELL	OTHER	P & A					7. UI	VIT AGREEMENT NA	M E	-
2.	NAME OF OPERATOR							8. FA	RBI OR LEASE NAM	E	-
		Coleman	0il & G	as. Inc.					BOC		
3.	ADDDESS OF OPERATOR			Place, N.	E.			9. W	ELI. NO.		-
		Albuquer	oue. Ne	w Mexico	87109_	, and the general light and statement of a polycle and table in the contract of the contract o	rans or superior of the ord		1-Y		
4.	LOCATION OF WELL (Repor See also space 17 below.) At surface	t location cles	rly and in a	ccordance with	any State rec	uirements.		10. <b>s</b>	WILDCAT	WILDCAT	
		1650	)' FSL,	810'FWL		$S_{i,j}^{(i)}$ , $C_{i,j}^{(i)}$		11. s	EC., T., R., M., OR B. SURVEY OR ARDA	LK. AND	-
						<u> </u>	. Augustosia	Sec	10, T22N,	RlW	
14.	PERMIT NO.		15. ELEVATION	NS (Show whether	r DF, RT, GR, e	te.)	V 13.	12. c	OUNTY OR PARISH		-
				77	677 Gr.	A 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		Sa	ndoval	New Mexi	co

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:					SUBSEQUENT REPORT OF:				
TEST WATER SHUT-OFF		PULL OR ALTER CASING			WATER SHUT-OFF		REPAIRING WELL		
FRACTURE TREAT		MULTIPLE COMPLETE	_	ļ	FRACTURE TREATMENT		ALTERING CASING		
SHOOT OR ACIDIZE		ABANDON*	X		SHOOTING OR ACIDIZING		ABANDONMENT*		
REPAIR WELL		CHANGE PLANS		1	(Other)				
(Other)			<u>  _                                   </u>		(Note: Report rest Completion or Reco	ılts of multiple mpletion Report	completion on Welt and Log form.)	d	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*


Propose to plug & abandon as follows:

Cement squeeze perfs 2808 to 2996 leaving cement plug in casing from 2700 to 2996.

Place cement plug in casing 1300-1400.

Back off 1 joint 2-7/8 casing and place cement plug in anulus from 150 back to surface.

Proceedure verbally approved: Richard Bell, 9:00 AM on 8-25-1981.



(This space for Federal or State

CONDITIONS OF APPROVAL, IF ANY:

18. I hereby gertify that the

APPROVED BY

SIGNED

\*See Instructions on Reverse Side

TITLE

TITLE

NMOCC