

SUNDRY NOTICES AND REPORTS ON WELLS

1. oil ☒ gas ☐ other

Aztec Energy Corporation

P. O. Box 2637, Farmington, N. M. 87401

AT SURFACE: 790' FNL and 950' FWL
AT TOP PROD. INTERVAL: 790' FNL and 950' FWL
AT TOTAL DEPTH: 790' FNL and 950' FWL

SUBSEQUENT REPORT OF:

(other)

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Spud well at 1100 hrs. 10/31/81. Drilled a 4-3/4" hole to 90', reamed hole to 12-1/4" hole and drilled to 280'. Ran 260' of 8-5/8" 24#/ft. X-42 casing and landed @ 273' KB. Cemented with 250 sks. class "B" with 2% CaCl₂ and 1/4 #/sk. Flocele. Good circulation throughout job, cement circulated to surface. Plug down @ 0100 hrs 11-6-81. W.O.C. 12 hours. Commenced drilling 7-7/8" hole.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. [Signature] TITLE V.P. of Operations DATE 3-16-82

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY _____

ACCEPTED FOR RECORD

MAR 18 1982

EASINGTON DISTRICT

BY

5m 2m