PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON\* (other)

DISTRICT ENGINEER

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Dec. 1973	DOUBE: DO: 42-11424
UNITED STATES DEPARTMENT OF THE INTERIOR	<b>5. LEASE</b> 09-000162
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Contract #162
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a difference, use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil page gas	Jicarilla L
well well other	9. WELL NO.
2. NAME OF OPERATOR  Mobil Producing TX. & N.M. Inc.  3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Wildcat
9 Greenway Plaza, Ste. 2700, Houston, TX 770	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space below.)	
AT SURFACE: 990 FNL & 990 FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as surface	Sandoval New Mexico
AT TOTAL DEPTH: Same as surface	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOT	
REPORT, OR OTHER DATA	15. FLEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	
TEST WATER SHUT-OFF FRACTURE TREAT	
SHOOT OR ACIDIZE	
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
- Set retainer @ 7400'. Squeeze 100 sx and leave 25 sx on top of retainer to 7070'.
- GIH OE to 7390'. Spot 25 sx Class B neat to 7060' to isolate Dakota.
- 3. PU to 5060' & spot 25 sx Class B neat to 4730 to isolate Mesaverde.
- 4. PU to 3244' & spot 115 sx Class B neat to 2680' to isolate liner top & Ojo Alamo.
- 5. PU to 500' and spot 30 sx Class B neat to 400'.
- Spot surface cement and set marker.

Subsurface Safety Valve: Manu. and Type	B	Set @ Ft.
18. I hereby certify that the foregoing is signed Laula A. Collim	true and correct	4-23-82
APPROVED BY	(This space for Federal State Office use)  TITLE  NMOCC	APPROVED  AS AMENDED  MAY 4 1982  ELECTIFICATION

\*See Instructions on Reverse Side