UNITED STATES

| DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY | NM 37548 6. IF INDIAN, ALLOTTEE OR TRIBE NAME None 7. UNIT AGREEMENT NAME None 8. FARM OR LEASE NAME Lewis 1-20-3 | | |
|---|--|--|--|
| SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug-back to a different esservoir, Use Form 9-331-C for such proposals.) | | | |
| 1 all gas | | | |
| well Well other 2. NAME OF OPERATOR | 9. WELL NO. 2 | | |
| Lewis Energy Corporation 3. ADDRESS OF OPERATOR | 10. FIELD OR WILDCAT NAME Undesignated Gallup | | |
| 232 N. Schwartz, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 1 T20N R3W | | |
| AT SURFACE: 510' FSL 565' FEL Sec 1 T20N R3W AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same | 12. COUNTY OR PARISH 13. STATE New Mexico 14. API NO. | | |
| 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA | None 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6990' GR | | |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)Proposals to protect casing | (NOTE: Report results of multiple completion or zone change on Form 9–330.) | | |
| 17 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state | e all pertinent details, and give pertinent dates | | |

5. LEASE

including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Measures to protect the casing from electrolysis deterioration opposite the Menefee formation have been required by the M.M.S. As noted on Form 9-331 dated 2/2/82 and accepted for record on 2/16/82, this work must be performed by 2/16/83. Lewis Energy Corp. requests approval of one of the following proposals:

- To perform a cement squeeze to cover the Menefee formation and protect the casing from electrolysis deterioration.
- To install cathodic protection to the casing. This would consist of a system where an electrical current is applied to the casing and passed on to a shallow ground well.

Whichever method is accepted, it will be performed in accordance with sound and accepted engineering practices.

| Subsurface Safety Valve: Manu. and Type | | | Set @ | Ft. |
|--|---|-------------|---------|----------------|
| 18. I hereby certify that the foregoing is | true and correct | | | |
| SIGNED Zachary C. Jewis | TITLE Operations Mgr. | DATE | 2/24/82 | |
| | (This space for Federal or State office u | ıse) | | |
| APPROVED BY | TITLE | DATE _ | . Milit | ild for record |
| $\overline{}$ | 20000 | | • | 4000 |

NMOOR

WAR 03 1365