

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-0 for such proposals.)

1. oil ☒ well ☐ gas well ☐ other ☐
2. NAME OF OPERATOR
JACK A. COLE
3. ADDRESS OF OPERATOR
P. O. Box 191 Farmington, N.M. 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1850'FNL, 1850'FEL
AT SURFACE:
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
Contract No. 360
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Chacon Amigos
9. WELL NO.
8
10. FIELD OR WILDCAT NAME
Chacon Dakota Associated
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 1-T22N-R3W
N.M.P.M.
12. COUNTY OR PARISH
Sandoval
13. STATE
N.M.
14. API NO.
30-043-20603
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7229'G.L.

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

(other) Correcting 4-1/2" casing depth

RECEIVED

MAY 10 1982

GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Correct 4-1/2" casing depth

1/28/82 T.D. 7194'. Ran 231 joints 4-1/2", 10.50 & 11.60, K-55 casing (7185') set at 7194' with:

First Stage: 700 sacks 50-50 Pozmix with 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Calculated top of cement 1956'.

Second Stage: 150 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite followed by 50 sacks Class "B" cement. Top of cement Temperature Survey - 1770'. Stage Collar set at 2994'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

FOR: JACK A. COLE
18. I hereby certify that the foregoing is true and correct

Walsh Engr. & Prod.

SIGNED Dorothy Blacett TITLE Corporation DATE 5/4/82
Dorothy Blacett, Production Foreman

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

NMOCC

BY Snn