

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
JACK A. COLE

3. ADDRESS OF OPERATOR
P.O. Box 191 Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1850' FSL, 1850' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
FEB 17 1982
U.S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

5. LEASE
Contract No. 360

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Chacon Amigos

9. WELL NO.

7

10. FIELD OR WILDCAT NAME
Chacon Dakota Associated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 11-T22N-R3W

12. COUNTY OR PARISH
Sandoval

13. STATE
New Mexico

14. API NO.
30-043-20604

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7159' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/29/82 Spud Well

1/29/82 T.D. 270'. Ran 6 joints 8-5/8", 24.0, K-55 casing (253.29) set at 268.29 with 250 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Pressure test with 500 psig. Test ok.

2/14/82 T.D. 7000'. Ran 224 joints 4-1/2", 10.50 & 11.60, K-55 casing (7017.02') set at 7000' with:

First Stage: 700 sacks 50-50 Pozmix with 6-1/4" Gilsonite and 6 lbs. salt per sack. Calculated top of cement 1650'.

Stage II: 75 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite followed by 50 sacks Class "B" cement. Top of cement Temperature Survey - 2000'. Stage Collar 2750'

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

FOR: JACK A. COLE ORIGINAL SIGNED BY President, Walsh Engr.
SIGNED EWELL N. WALSH TITLE & Prod. Corp. DATE 2/16/82

Ewell N. Walsh, PE

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

FEB 22 1982

NMOCC

BY Dean Elliott
FARMINGTON DISTRICT