5 USGS

J Form Approved. ∖

Form 9-331 Dec. 1973

SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

REPAIR WELL

(other)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	Budget Bureau No. 42-R1424
	5. LEASE
١	NM 14729
-	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	7. UNIT AGREEMENT NAME
	8. FARM OR LEASE NAME
١	Husky Federal
	9. WELL NO.
1	
ļ	10. FIELD OR WILDCAT NAME
-	Undes. Pictured Cliffs
	11. SEC., T., R., M., OR BLK. AND SURVEY OR
	Sec 34 T21N R4W
	12. COUNTY OR PARISH 13. STATE NM
_	14. API NO.
	15. ELEVATIONS (SHOW DF, KDB, AND WD)

CE (Note teport results of multiple completion or zone change or Form 9–330.)

SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEI
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEA
1 -:1	Husky F
1. oil gas well other dry hole	9. WELL NO.
2. NAME OF OPERATOR	11
DUGAN PRODUCTION CORP.	10. FIELD OR WI
3 ADDRESS OF OPERATOR	Undes. F
P 0 Box 208, Farmington, NM 87401	11. SEC., T., R.,
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec 34
below.) AT SURFACE: 1850' FNL - 790' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR Sandoval
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS 7060'
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

U. S. GEOLOGICAL SURVEY

FARIAINGTON, N. M.

NOTE: VERBAL APPROVAL TO P & A RECEIVED 1-14-82 per Ken Townsend. Request approval to plug and abandon as follows:

- 1. Place cement plug from TD 1580' to 1300'.
- 2. Place cement plug from 1110' to 900'.
- 3. Place cement plug from 140' to surface.
- 4. Place drilling mud, 9.2#/gal, between plugs.
- 5. Install dry hole marker.

6. Restore surface.	Set @	Ft.
Subsurface Safety Valve: Manu. and Type		
SIGNED IN 1 Just Geologist DATE	1-14-82	
APPROVED BY CAN CLUST TITLE SENT STATE OFFICE USE)	JAN 18 1982	
CONDITIONS OF APPROVAL, IF ANY:		

MAN C

سايه

------ on Payarea Sida

UME CON. COM. DIST. 3