ABANDON\*

## UNITED STATES

Change Surface Hole & Csg.

DEPARTMENT OF THE INTERIOR	Contract #393  6. IF INDIAN, ALLOTTEE OR TRIBE NAME  Jicarilla			
GEOLOGICAL SURVEY				
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME  8. FARM OR LEASE NAME			
reservoir. Use Form 9–331–C for such proposals.)				
1. oil gas gas	Jicarilla 393			
well gas well other	9. WELL NO.			
2. NAME OF OPERATOR	B-1			
Robert L. Bayless	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR	Ballard Pic. Cliffs			
P.O. Box 1541, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY O			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	$\hat{\mathcal{O}}_{Sec.}^{AREA}$ Sec. 21, T23N, R4W			
AT SURFACE: 790' FSL & 1850' FEL	12. COUNTY OR PARISH 13. STATE			
AT TOP PROD. INTERVAL: Same	Sandoval N.M.			
AT TOTAL DEPTH: same	14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,				
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD 7007' GL			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:				
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES  THE COMPLETE DIVIDING 1982	(NOTE: Report results of multiple completion or zon change on Form 9–330.)			

5. LEASE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Will change surface hole and casing size as follows:

from 12-1/4" hole to 9" hole; from 8-5/8" casing to 7", 23# casing.



Subsurface Safety Valve: Manu. and Type				Set @ Ft.	
18. I hereby certify that the foreg	oing is true and correct	Engineer	DATE	June 8, 1982	
	(This space for	Federal or State office	use)		
APPROVED BY	TITLE _		DATE	/ COPPY <b>F</b> R FAR RE <b>CORN</b>	

\*See Instructions on Reverse Side