

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Chace Oil Company, Inc.
3. ADDRESS OF OPERATOR
313 Washington, SE, Albuquerque, NM 87108
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
Unit "K" 1850' FSL & 1850' FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
Contract #54
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Jicarilla Tribal Contract #54
9. WELL NO.
54-11
10. FIELD OR WILDCAT NAME
Chacon Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 3, T22N, R3W
12. COUNTY OR PARISH
Sandoval
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7230 KB

Progress Report ☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 164 joints of 4½", 11.6# casing. Set at 7141' KB. Shoe set at 4342'. Float collar at 7097'. D. V. Tool at 2755'. Cement baskets at 6702', 6464', 2314' and 2138'. 1st stage: Cemented with 500 sxs 50/50 posmix. 2% gel, 6# salt per sack. Plugged down at 5:15 P. M. on June 24, 1982. Second stage: Opened D. V. Tool and circulated for 3 hours. Cemented with 450 sxs of 65/35 posmix. 12% gel, 6½# Gilsonite per sack, Followed by 50 sxs of Class B neat. Plugged down at 9:40 P. M., June 24, 1982. Circulated 11 bbls. of cement to surface. Release rig.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Roger M. Carey TITLE President DATE June 25, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

MMOCC

JUL 7 1982

SM