

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Robert L. Bayless

3. ADDRESS OF OPERATOR
P.O. Box 1541, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 790' FSL & 790' FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
Contract 393

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jicarilla 393

9. WELL NO.
B #3

10. FIELD OR WILDCAT NAME
Ballard Pic. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 22, T23N, R4W

12. COUNTY OR PARISH
Sandoval

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7038' GL

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Spud/set surface csg.

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 01 1984

BUREAU OF LAND MANAGEMENT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-28-84 Spud well at 10:00 p.m. Drilled 127 ft. of 9-7/8" surface hole. Ran 124 ft. of 7", 20#/ft., J-55 used surface casing and set at 126 ft. Rigged up Cementers Inc. Cemented surface casing with 40 sacks Class "B" cement w/2% CaCl₂. Good circulation throughout job. Circulated cement to the surface. Plug down at 2:00 a.m. on 4/29/84. WOC 8 hrs.

4-30-84 Drilling @ 1256 ft. Deviation 1/2° at 1225 ft.

RECEIVED
MAY 10 1984
OIL CON. DIV.
Set @ DIST. 3 Ft.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Norm H. McLeod TITLE Engineer DATE 4/30/84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 09 1984

*See Instructions on Reverse Side

NMOCC

FARMINGTON RESOURCE AREA
PV 5mm