,	UNITED STATES SUBMIT OF THE INTERIOR VETSE BIS UREAU OF LAND MANAGEMENT	Form approved. Budget Bureau No. 1004—0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SHELL NO. NM-36936
	NOTICES AND REPORTS ON WELL proposals to drill or to deepen or plug back to a differ PPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTER OR TRIBE NAME
1. OIL XX GAS		7. UNIT AGRBEMENT NAME
2. NAME OF OPERATOR	N 8 8	S. FARN OR LEASE NAME
Gary-Williams Oil Producer, Inc.		San Isidro 15
3. ADDRESS OF OPERATOR		9. WELL NO.
4. LOCATION OF WELL (Report locations)	Drive East, Englewood, CO 80112 tion clearly and in accordance with any State requirem	ents.* 10. FIBLD AND POOL, OR WILDCAT
See also space 17 below.) At surface 1650 FNL	and 1980' FEL Section只是2例-建了	VFD Rio Puerco Mancos
*		SURVEY OR AREA
	* AUG 1 41	984 SW NE 15-20N-3W
14. PERMIT NO.	15. BLEVATIONS (Show Wighter Avg 19 FOR Mill D N	MANAGEMENT 12. COURTY OR PARISE 13. STATE
	6835' GR	Sandoval NM
	k Appropriate Box To Indicate Nature of No	tice, Report, or Other Data
NOTICE OF	INTENTION TO:	SUBSECURNT REPORT OF:
TEST WATER SHUT-OFF		EBUT-OFF REPAIRING WELL
BROOT OR ACIDIZE		RE TREATMENT ALTERING CASING ABANDONMENT*
REPAIR WELL	CHANGE PLANE (Other)	Court of Court of Contract Of
(Other)	' Co	OTE: Report results of multiple completion on Well empletion or Recompletion Report and Log form.)
/ DASTRICE PROPOSED OR COMPLET: proposed work. If well is conent to this work.)	ED OPERATIONE (Clearly state all pertinent details, and ; lirectionally drilled, give subsurface locations and measu	give pertinent dates, including estimated date of starting any ired and true vertical depths for all markers and sones perti-
Joints 9-5 Float set 10% salt, with 100 s. (83 cu ft) Released p strength in	shoe, shoe joint (centralized at /8" casing (total 12 joints, tall at 454'. Cemented with 150 sx (49 6-1/4#/sx gilsonite, 0.6% Halad-9 x (118 cu ft) Class B, 2% CaCl 1 to pit. Final pump pressure 250 ressure, held OK. Job complete an 12 hours 555 psi, in 24 hours 1 is at the surface.	y: 481.83'). Set at 494' KB. B cu ft) 65/35 pozmix, 12% gel, , and 1/2#/sx flocele. Followed 00% returns, Circulate 25 sx psi. Bumped plug to 800 psi. t 6:45 a.m. 8/7/84. (Compressive
	•	RECEIVEM
		AUG22 1984
		OIL CON. DIV.
		DIST. 3
s. I hereby certify that the forego	ing is true and correct	- •
SIGNED Zay 1400	TITLE Operations	Superintendent DATE 8/7/84
(This space for Federal or Stat		ACCEPTED FOR RECORD
APPROVED BY	MINT I	
CONDITIONS OF APPROVAL,	IF ANY:	AUG 2 1 1984
	NMOCC	rn art
	*See Instructions on Revene S	FARMINGTON NEGOTING AKLA