

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS

5. LEASE DESIGNATION AND SERIAL NO.

NM-23230

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

CEJA PELON

9. WELL NUMBER

28-14

10. FIELD AND POOL, OR WILDCAT

Rio Puerco - Mancos

11. SEC., T., R., OR BLK. AND SURVEY

SECTION 28 - T21N - R4W

14. PERMIT NO.

15. ELEVATIONS

6992' GL 7004' KB

12. COUNTY OR PARISH

SANDOVAL

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON ☐
REPAIR WELL ☐ CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIR WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT ☒
(OTHER) ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS

Contacted BLM and commenced to rig up on 5-16-94. Pumped 56 Barrels of fluid from Ceja Pelon #35-13 into Ceja Pelon #28-14. Picked up tubing and ran into hole to 4,421'. Rigged up to pump cement. Pump 10 BBIs into tubing and tubing pressured up. Pulled 4 joints of tubing and still could not pump down tubing. Tripped out of hole with tubing. The 69th joint down was plugged with paraffin. Pumped 10 barrels down the remaining tubing to insure it was clean. Tripped into hole with tubing to 4427'. Cemented bottom plug from 4421' to 4221' with 60 sacks of cement. Displaced with 14 barrels of water. Pulled 30 joints of tubing. Shut down overnight to wait on cement. Tripped in hole with tubing and tagged plug 4041' on the morning of 5-17-94. Bottom plug from 4421' to 4041'. Tripped out of hole laying down tubing to 1603'. Loaded hole with 80 barrels and circulated oil out of hole. Cemented middle plug from 1603' to 1500' with 29 sacks of cement. Displaced with 5.6 barrels of water. Tripped out of hole laying down tubing. Rigged up wireline and perforated 4 holes in 7" casing at 257'. (A collar was located at 255'.) Cemented top plug from 257' to surface in 9-5/8" and 7" annulus and inside 7" with 95 sacks of cement. Nipped down BOP and cut off wellhead. Erected dry hole marker. Returned tubing to yard in Cuba, NM. Release Rig. Well P&A'ed 5-17-94. Plugging witnessed by Al Luna of the BLM office located in Cuba, NM.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Samuel Gary, Jr.
Attorney-in-Fact

DATE

May 24, 1994

(This space for Federal or State office use)

APPROVED BY

TITLE

Acting Chief, Lands and Mineral Resources

DATE

JUN 27 1994

CONDITIONS OF APPROVAL, IF ANY:

113000