

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

6. LEASE DESIGNATION AND SERIAL NO.

NM-37548

7. IF INDIAN, ALIQUOT OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

8. UNIT SUBSIDENCE NAME

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling

9. FARM OR LEASE NAME

Federal 22-1

2. NAME OF OPERATOR

Champlin Petroleum Company

3. ADDRESS OF OPERATOR

P. O. Box 1257, Englewood, CO 80150

10. WELL NO.

2

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
Also show depth of well below.)
At surface

SENE (1650' FNL & 1980' FWL)

FEB 04 1985

11. FIELD AND POOL, OR WILDCAT

Rio Puerco-Mancos ~~Gallop~~

12. SUB. T. S. N. OR B.L. AND
SUBST. OR ADD.

Section 1-T20N-R3W

13. PERMIT NO.

Approved 12-14-84

14. ELEVATIONS (Show whether of, to, or, etc.)

7,020' Graded GR., 7031' KB

15. COUNTY OF PABLO

Sandoval

16. STATE

N. Mexico

17. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDISE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDISING

(Other) Operations

REPAIRING WELL

ALTERING CASING

ABANDONMENT

X

(Note: Report results of multiple completion on Well
Completion or Recombination Report and Log form.)

18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and source perforations to this work.)

Rigged up Four Corners Rig #5. Spudded 12 1/4" hole @ 1:00 p.m. 1-24-85. Drilled to 515'. Ran 13 jts. 9-5/8" 36# K-55 ST&C casing, shoe @ 510', baffle @ 475'. Ran centralizers on bottom 3 jts. Rigged up Dowell. Cemented w/275 sx (440 CF) 50-50-2 Poz, 2% C-20, 2% CaCl2, 1/4#/sx Check Flow. Circulated 5 bbls cement to surface. Plug down @ 10:30 p.m. 1-24-85. WOC 12 hours. Drilled cement and shoe. Drilled 8-3/4" hole to 515' to 3815'.

Present Operations: Drilling.

DEN. REG. DRILLING

FEB 28 '85

RECEIVED
MAR 06 1985
OIL CON. DIV.
DIST. 3

ACTION INFORMATION

RAS

RJR

CMM

FILE

19. I hereby certify that the foregoing is true and correct

SIGNED Ramona J. Rhoden

TITLE Sr. Engineering Aide

DATE 1-29-85

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE
FEB 21 1985

*See Instructions on Reverse Side

NMOCC

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.