Form 3160-5 (June 1990)

# **UNITED STATES** DEPARTMENT OF THE INTERIOR

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

	BUREAU OF LAND MANAGEMENT	
SUNDRY NOTICES	NMNM99702  6. If Indian, Allottee or Tribe Name	
Do not use this form for proposals to d Use "APPLICATION FO	6. If Indian, Allottee or Tribe Name	
SUBMI	7. If Unit or CA, Agreement Designation	
1. Type of Well  Soli Gas Well Other		8. Well Name and No.
2. Name of Operator		San Isidro #26-7
High Plains Petr	9. API Well No.	
3. Address and Telephone No.	30-043-20748  10. Field and Pool, or Exploratory Area	
3860 Carlock Dr., Boulde 4. Location of Well (Footage, Sec., T., R., M., or Survey	Rio Puerco Menefee	
		11. County or Parish, State
1900' FNL & 2250' FEL Sec. 26, T20N, R3W, NMPM		Sandoval County, New Mexico
2. CHECK APPROPRIATE BOX	((s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
X Notice of Intent	X Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
Π	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing Other	Conversion to Injection Dispose Water
	C Out	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
vive subsurface locations and measured and true ver-		ng any proposed work. If well is directionally drilled
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v t. A well diagram is attached.	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques wants done by June firs	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v	
Instructions are reques wants done by June firs	tical depths for all markers and zones pertinent to this work.)*  ted for the abandonment of the v t. A well diagram is attached.	
Instructions are reques wants done by June firs.  14. I hereby certify that the foregoing is true and correct	ted for the abandonment of the vt. A well diagram is attached.  Petroleum Engineer	vell, which the OCD

# Well Diagram Jan Island #26-7 Prepared by: 1. Somers

	Prepared by: J. Somers		
		16"75#K55 set @97' and contol. W7 175 2x C/A rest	
de la recentación de	NAAN AND AND AND AND AND AND AND AND AND	95/8"36#U5555t@ 214' W16037 CB cont, 27, CaCl2	
	The same in the sa		
	A Addition of the Control of the Con		
197			
	7(1)24		
	2 mary 1		
	Andreas		
	CALL COLOR OF THE CALL COLOR O		
	Per Carabana		
	A Company of Company o		
	in the street	# Additional Menetes pts 2188 22081 - tipt	
	en and charter a	CIBPEZZO	
		= Original MeneFee pfs - 1/2pf 2272-82', Reperf'd 2273-82'wayof	
	The state of the s	CIBP@ 2340'	
p-10			
<b>H</b> . 1			
		Top 4/2" Iner 3077!	
TOO OF OW			
Top of ow 340' (in the	1")_4	10,000 sof of N2, 150 or CIB w729, C. CI2 + 25 ex CIB w737. C.Cl. Note: Designed to coment into the surface asg.	
		Note: Designed to coment into the surface asg.	
CI BP@36	W   S		
un top		Gallup pfs 3624-8935 m 15 holes	
		45" 105# 155 sol@ 41791 and cottled was 130 sx, 50-50 pez. cont 2200	
	1	and the same	

### UNITED STATES DEPARTMENT OF THE INTERIOR

## BUREAU OF LAND MANAGEMENT Albuquerque Field Office 435 Montano N.E. Albuquerque, New Mexico 87107

Company High Plains Petroleum Corporation.

Well No. San Isidro No. 26-71

Location 1900' FNL & 2250' FEL Sec.26, T20N, R3W, NMPM

Lease No. NMNM-99702

Government Contacts:

Bureau of Land Management, Albuquerque Field Office Office 505.761.8700

Manager: Steve Anderson, Assistant Field Manager 505.761.8982

Petroleum Engineer: Brian W. Davis 505.761.8756, Home 505.323-8698,

Pager 505.969-0146, Cell 505.249.7922,

Petroleum Engineering Technician: Al Yepa 505.252.6981 and 505.289.3748 Patricia M. Hester 505.761.8786

BLM Geology / Environmental Contact:

### **GENERAL REQUIREMENTS** FOR OIL AND GAS OPERATIONS ON FEDERAL AND INDIAN LEASES

- 1. Plugging operations authorized are subject to the "General Requirements for Permanent Abandonment of Wells on Federal and Indian Leases."
- 2. For wells on Indian leases, Bryce Hammond with the Jicarilla Nation Tribal Oil and Gas Office is to be notified at least 24 hours (48 hours if possible) before the plugging operations commence. His phone number is (505) 759-1823, x-31 office, (505) 320-9741 cell. Office hours are 7:45 a.m. to 4:30 p.m.
- 3. Blowout prevention equipment is required.
- 4. The sundry is approved with the following requirements:

Plug 1: 2250 - 2088 (162') 18 cf (21 sacks)

Plug 2: 1880-1780 (100') 11 cf (13 sacks)

Plug 3: 1200-1100 (100') 11 cf

Plug 4: 840-740 (100') 11 cf

Plug 4: 450-350 (100') 11 cf

Plug 6: 254-0 (254') 28 cf (24 sxs)

Cement Plugs include 50% excess, Class B 1.18 yield

Cutoff below surface and install dryhole marker.

Note: Plugs can be combined but the intervals listed must be covered. BWD

### BLM CONDITIONS OF APPROVAL

The following surface rehabilitation Conditions of Approval must be complied with as applicable, before this well can be approved for final abandonment (see 43 CFR 3162.3-4). Surface rehabilitation work shall be completed within one year of the actual plugging date. Notification for completion of this work should be submitted with a Sundry Notice. Questions? Call Pat Hester at (505) 761-8786.

- 1. All fences, production equipment, purchaser's equipment, concrete slabs, deadman (anchors), flowlines, risers, debris and trash must be removed from the location. Non-retrieved flowlines and pipelines will be abandoned in accordance with State Rule 714. Information supporting the non-retrieval will be included in the subsequent report or final abandonment Sundry Notice.
- 2. Production pits will be closed according to the Unlined Surface Impoundment Closure Guidelines, as approved in the Environmental Assessment of December 1993. Any oil stained soils can be remediated on-site according to these guidelines or disposed of in a an approved facility.
- 3. The well pad will be shaped to the natural terrain and left as rough as possible. All compacted areas and areas devoid of vegetation shall be ripped to a minimum of 12" in depth before reseeding.
- 4. Access roads will be shaped to conform to the natural terrain and left as rough as possible to deter vehicle travel. Access will be ripped to a minimum of 12" in depth, water barred and reseeded. All erosion problems created by the development must be corrected prior to acceptance of release. Water bars should be spaced as shown below along the fall line of the slope:

% Slope	Spacing Interval
Less than 20%	200'
2 to 5 %	150'
6 to 9 %	100'
10 to 15 %	50'
Greater than 15%	30'

- 5. All disturbed areas will be seeded with the prescribed certified seed mix (reseeding may be required). Seed mix must be certified weed free to avoid the introduction of noxious weeds. Refer to the original APD for seed mix.
- 6. Notify Surface Managing Agency seven (7) days prior to seeding so that they may be present to witness.
- 7. The period of liability under the bond of record will not be terminated until the well is inspected and the surface rehabilitation approved.

Other Surface Managing Agencies (SMA's) may vary slightly in their restoration requirements. It is your responsibility, as the operator, to obtain surface restoration requirements from other SMA's. We need to be provided with a copy of these requirements. Any problems concerning stipulations received from other SMA's should be brought to us. On private land, a letter from the fee owner stating that the surface restoration is satisfactory will be provided to the office. Questions? Call Pat Hester at (505) 761-8786.