

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. LEASE IDENTIFICATION AND SERIAL NO.
NM-24442
7. INDIAN, ALIEN, OR TRUST NAME
8. UNIT ABBREVIATION NAME
9. FARM OR LEASE NAME
Federal 41-20
10. WELL NO.
1
11. FIELD AND POOL, OR WILDCAT
Wildcat
12. SEC., T., S., R., OR BLS. AND
SUBST. OR AREA
Sec. 20-T18N-R3W
13. COUNTY OR PARISH
Sandoval
14. STATE
N. Mexico

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling

2. NAME OF OPERATOR

Champlin Petroleum Company

3. ADDRESS OF OPERATOR

P. O. Box 1257, Englewood, CO 80150

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

At surface

NENENE (490' FNL & 420' FEL)

15. PERMIT NO.

Approved 3-22-85

16. ELEVATIONS (Show whether OF, BT, OR, etc.)

6572' GR, 6584' KB

17.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TREAT

SHOOTING OR ACIDIZING

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON

CHANGE PLANT

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

Operations

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and tubes pertinent to this work.)

PTD 1800'. WOC 12 hours. Pressure tested casing to 1500 psi for 30 minutes. Held OK. Drilled 40' of cement and shoe joint. Drilled 6-1/4" hole 1800' to 2700'. Ran DIL-GR and CDL-SNL-GR 2700' to 1800'. Ran 64 jts 4-1/2", 11.6#, K-55 LT&C casing, shoe @ 2700', Float collar @ 4656'. Ran 1 centralizer/joint on bottom 4 jts and every other joint up to 1800'. Cemented w/10 bbls chemical wash, 125 sx (151 CF) 50-50 Poz w/2% D-20, 10% D-44, 1% D-112. Displaced w/water. Bumped plug w/900 psi. Floats held. Set 40,000# on slips. Released rig @ 5:00 a.m. 4-3-85.

Present operations: Waiting on completion.

RECEIVED
APR 16 1985
OIL COM. DIV.
DIST. 6

19. I hereby certify that the foregoing is true and correct

SIGNED

Ramona J. Rhoden

TITLE

Sr. Engineering Aide

DATE

4-3-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APR 15 1985

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any Department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

111000