

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM-24442

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Drilling

2. NAME OF OPERATOR
Champlin Petroleum Company

3. ADDRESS OF OPERATOR
P. O. Box 1257, Englewood, CO 80150

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

NENENE (490' FNL & 420' FEL)

14. PERMIT NO.
Approved 3-22-85

15. ELEVATIONS (Show whether DT, ST, OR, etc.)
6572' GR

6. FARM OR LEASE NAME
Federal 41-20

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC. T. R. S. OR BLM. AND
SUBST. OR AREA
Section 20-T18N-R3W

12. COUNTY OR PARISH
Sandoval

13. STATE
N. Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETION ☐
ABANDON ☐
CHANGE PLANT ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) Operations

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT? ☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Moved in and rigged up Four Corners Rig #5. Spudded 12-1/4" hole @ 6:00 p.m. 3-29-85. Drilled 12-1/4" hole to 145'. Ran 3 jts 9-5/8" 36# K-55 ST&C casing, shoe @ 140'. Cemented w/120 sx (163 CF) Class B w/2% CaCl₂, 1/4#/sx Flocele. Circulated cement to surface. Plug down @ 12:00 a.m. 3-30-85, WOC 12 hrs. Nippled up BOP's, tested to 1500 psi. Held OK. Tagged cement @ 100'. Drilled 8-3/4" hole 145-1800'. Ran DIL-SFL-SPGR, FDC-CNL-GR, and BHC-Sonic logs from 1800' to surface pipe. Ran 46 jts 7", 23#, K-55, ST&C casing, shoe @ 1801', FC @ 1763'. Cemented w/10 bbls mud wash, 150 sx (252 CF) Lite-5 w/4% gel, 6-1/4#/sx D-42, 1/4#/sx D-29. Tailed in w/150 sx (177 CF) Class B, 2% CaCl₂, 1/4#/sx D-29. Bumped plug w/1200 psi. Circulated 10 bbls to surface. Set 40,000# on slips.

Present Operation: Waiting on cement.

APR 10 1985
OIL CORP. INC.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED Ramona J. Rhoden TITLE Sr. Engineering Aide DATE 4-02-85
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APR 10 1985

*See Instructions on Reverse Side
NMOCC

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.