## UNITED STATES DEPARTMENT OF THE INTERIOR

5. LEASE DESIGNATION AND SERIAL NO.

[]

BUREAU		NM-24450		
SUNDRY NOTICES AND REPORTS ON WELLS			6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
1.			7. UNIT AGREEMENT NAME	
OILWELL [] GAS WELL [X] OTHER	·			
2. NAME OF OFFICE OF CONTROL OF C			8. FARM OR LEASE NAM	E
		Ceja Pelon		
3. ADDRESS OF OPERATOR 1775 Sherman St., Ste 1925			9. WELL NUMBER	
Denver, CO 80202 (303) 831-4673			#6 - 13	
4. LOCATION OF WELL		10. FIELD AND POOL, OR WILDCAT		
AT SURFACE			Undesignated Chacra	
790' FSL, 870' FWL Section 6-T21 N-R4W		11. SEC., T., R., OR BLK. AND SURVEY		
			SECTION 6 - T21N	- R4W
14. PERMIT NO.	15 ELEVATIONS	- <del>-</del>	12. COUNTY OR PARISH	13. STATE
	7110' GL		SANDOVAL	N.M.
16. Check Appi	ropriate Box To Indicate Na	ture of Notice, Report, or (	Other Data	
		SUBSEQUENT REF	PORT OF:	
TEST WATER SHUT-OFF [ ] PULL OR ALTER CASING []		WATER SHUT-OFF [ ]	REPAIR WELL []	
FRACTURE TREAT [ ] MULTIPLE COMPLI	ETE []	FRACTURE TREATMENT []	ALTERING CASING []	
SHOOT OR ACIDIZE [ ] ABANDON	[X]	SHOOTING OR ACIDIZING []	ABANDONMENT []	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS

REPAIR WELL []

OTHER []

Request approval to abandon well per the attached procedure.

CHANGE PLANS

[]

DECEIVED OCT 2 6 1994 OIL COM. DIV. DIST. 3

18. I hereby certify that the foregoing strue and correct  SIGNED ALL STRUE ANTILE ANTILY - in - fact  DATE 2 May 94	
(This space for Federal or State Office use Acting Chief, Lands and Federal Pescurose OCT 2 0 1994  APPROVED BY PATRICIA M HOSER TITLE	
CONDITIONS OF APPROVAL IF ANY:	

## CEJA PELON #6-13 Plug and Abandon Procedure

## SEE ATTACHED WELL DIAGRAM FOR TUBULAR DETAILS

- 1. Move in, rig up, service rig.
- 2. Pump tank bottoms into well.
- 3. Nipple up BOP's. Pick up tubing string and TIH to 2050'. Fill hole with gelled water.
- 4. Set Class "H" cement plugs as follows: Plug #1, 25 sacks (30 cu. ft.) @ 2050'. Plug #2, 25 sacks (30 cu. ft.) from 197' to surface.
- 5. Cut off casing below ground level and erect dry hole marker.
- 6. Remove production equipment and reclaim location to BLM specifications.

March 31, 1994 Charles H. Johns

## Samuel Gary. Jr. & Associates

Ce ja Pelon 6-13 Wellbore Diagram SWSW Sec. 6 T2IN R4W Sandoval County. NM

Casing cemented w/ 200 sx Class B

Ground ele. 7110°

—l2 I/4" hole

8 5/8". 24 lb/ft surface csg @ 197"

-6 3/4" hole

4 1/2" Casing Breakdown

Interval	Weight	Grade	Conn.	
0'-2345'	10.5	J-55	ST&C	•

Cemented with 200 sx 50/50 Pozmix and 200 sx Class B.

Cement circulated to surface

Chacra perfs at 2078', 210', 218', 2131', 2138', 2142', 2188', 2202'

-4 1/2" Casing at 2345'

TD at 2379°

PREPARED BY: S.C. FREDRICKSON PREPARED ON: 5/28/92