

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0145
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM - 25295

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

DIVIDE

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 31, T-21-N, R-3-W

NMPM

12. COUNTY OR PARISH 13. STATE

SANDOVAL

NM

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

7081' GR

14. PERMIT NO.

15. ELEVATIONS (Show whether D.P.M. or S.C.)

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) SPUD & CASING REPORT

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. REPORT ON USE OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

SPUDDED WELL ON 5-23-85.

DRLD 12 1/4" HOLE TO 348'. RAN 9 5/8", 36#, K-55 CASING & CEMENTED @ 336' W/160 SKS CL B CEM W/2% CACLz. CIR CEM TO THE SURFACE. PD 9:00AM 5-24-85.
1892f.

PRESSURE TESTED CASING & BOP TO 1500 PSI FOR 30 MIN - O.K.

DRLD 8 3/4" HOLE TO 4200' - RAN IES, GR, CDL & CNL LOGS.

RAN 7", 23# & 26#, K-55 & N-80 CASING & LANDED @ 4199'. CEMENTED IN 2 STAGES.
STAGE #1 275 SKS OF PACESETTER LITE W/6# HI-SEAL PER SK FOLLOWED BY 50 SKS CL B W/6# HI-SEAL PER SK. (499 CU FT.)
STAGE #2 (STAGE TOOL @ 2240') 150 SKS OF PACESETTER LITE W/6# HI-SEAL PER SK FOLLOWED BY 50 SKS CL B CEM W/2% CACLz. (299 CU FT.) PLUG DOWN 3:30 AM 5-30-85
GOOD CIRC THROUGH OUT BOTH STAGES OF CEM JOB.

PRESSURE TESTED 7" CASING & BOP TO 1500 PSI FOR 30 MIN - O.K.

DRLD 6 1/4" HOLE W/AIR TO TOTAL DEPTH OF 5600'. - RAN GR, IEL, CDL & TEMP LOGS.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

PRESIDENT

DATE 6-10-85

(This space for Federal or State office use)

APPROVED BY

TITLE

JUN 13 1985

DATE

CONDITIONS OF APPROVAL, IF ANY:

OIL CON. DIV.
DIST. 3.

*See Instructions on Reverse Side

NMOCC

The Federal Anti-Trust Act, Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the Federal Government, or to any officer or employee thereof, any false or fraudulent statements or representations as to any matter within its jurisdiction.