

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM-38276

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

WELL ☐ GAS WELL ☐ OTHER ☒ Drilling

JUN 03 1985

2. NAME OF OPERATOR

Champlin Petroleum Company

3. ADDRESS OF OPERATOR

P. O. Box 1257, Englewood, CO 80150

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
For also space 17 below.)

At surface

SWSW (660' FSL & 660' FWL)

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

5. IF INDIAN, ALIQUOTEE OR TRIBE NAME

7. UNIT SUBSIDENT NAME

8. FARM OR LEASE NAME

Pelto-Trend-Federal 14-14
(Cuba South Unit)

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLE. AND
SUBST. OF AREA

Section 14-T19N-R2W

14. PERMIT NO.

Approved 5-20-85

15. ELEVATIONS (Show whether OF, BY, OR, etc.)

6881' GR, 6880' Graded Gr, 6892' KB

12. COUNTY OR PARISH

Sandoval

13. STATE

N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TEST

SHOOT OR ACIDISE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON

CHANGE PLANT

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDISING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

Notice of Spud

XX

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting on proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Moved in and rigged up Four Corners Rig #10. Spudded 12 1/4" hole @ 2:00 p.m. 5-28-85. Drilled to 520'. Ran 13 jts. 9-5/8". 36#, K-55, ST&C casing. Float collar @ 472', shoe @ 520' (510.88').. Cemented w/324.5 CF (275 sx) Class "B" cement w/2% CaCl₂, 1/4#/sx Flocele. Good returns. Circulated 29.5 CF (25 sx) cement to surface. Plug down @ 11:30 p.m. 5-28-85. Bumped plug w/800 psi. WOC 12 hours. Tested BOP's to 2000 psi for 30 minutes.

Drilled 7-7/8" hole 520-1935'.

Present operations: Drilling.

RECEIVED
BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA
JUN 03 1985

18. I hereby certify that the foregoing is true and correct

SIGNED

Ramona J. Rhoden

TITLE Sr. Engineering Aide

DATE 5-30-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCC