

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | | | |
|--|--|---|-------------------------|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | | 5. LEASE DESIGNATION AND SERIAL NO. NM 25601 | |
| 2. NAME OF OPERATOR Hixon Development Company | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | |
| 3. ADDRESS OF OPERATOR P.O. Box 2810, Farmington, NM 87499 | | 7. UNIT AGREEMENT NAME | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL, 1980' FWL, Section 28, T 20N, R 2W | | 8. FARM OR LEASE NAME Hugh K. Foster | |
| 14. PERMIT NO. | | 9. WELL NO. 1 | |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6900' GLE | | 10. FIELD AND POOL, OR WILDCAT Wildcat (Gal) | |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 28, T 20N, R 2W | |
| | | 12. COUNTY OR PARISH San Juan | 13. STATE New Mexico |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

| |
|--|
| |
| |
| |
| |

PULL OR ALTER CASING

| |
|--|
| |
| |
| |
| |

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANE

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

| |
|--|
| |
| |
| |
| |

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilling Program

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

| |
|--|
| |
| |
| |
| |

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well at 3:15 PM on 6/10/85. Drilled 13-1/2" hole to 234' K.B. Ran 5 joints (216.97') of 9-5/8", 36#, 8 rd, ST & C surface casing with guide shoe on 1st joint. Pumped 165 sks (195 cu.ft.) of Class "B" cement containing 2% CaCl. Displaced cement 30' short of casing shoe with 14.5 BW. Circulated 8 bbl. cement to surface. Shutdown and WOC 12 hours. Casing shoe set at 231.30'

CONFIDENTIAL

18. I hereby certify that the foregoing is true and correct

SIGNED Bruce C. Delventhal

TITLE Petroleum Engineer

DATE June 11, 1985

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side

NMOCC