(November 1983) (Formerly 9-331)		33) 331)	DEPARTMENT OF THE INTERIOR (Other lastroctions on re-					Expires August 31, 1985 5. LEASS DESIGNATION AND SERIAL NO. #390		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deopen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)								Jicarilla Apache		
1	OIL CAS OTHER Comingled							T. UNIT AGREEMENT NAME		
2.	HAMS OF OP		Martin	& Associates, I	nc.			8. FARM 68 LBASS M	AMS	
3.	ADDRESS OF OPERATOR							9. WILL BO,		
4	709 North Butler Farmington, NM 87401 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)							#62 Martin-WHittaker		
	790' FNL & 790' FWL							S. Lindrith Gallop Dakota		
	AUG 0 5 1985							NW/NW Sec. 23 T23N R4W		
14	PERMIT FO.			16. BLEVATION	SHEET C	MOTON PERMANAGEMENT		12. COURTY OR PARIS		
					46'	TON RESOURCE AREA		Sandoval	NM	
16	Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data									
	ROTICE OF INTENTION TO:							BFT ABPORT OF:		
	TEST WATER			PULL OR ALTER O		WATER SHUT-OFF	_	BRPAIRIFG		
	SHOOT OR A			ABANDON*		PRACTURE TREATME.		ALTERING ARANDONN		
	REPAIR WEL	L		CHAPGE PLANS		(Other) Squee	ze trea	tment	X	
7	Other) (Norm: Report results of multiple completion on Wall Completion or Recompletion Report and Log form) OUSCRIBE PROPOSED ON COMPLETED OPERATIONS (Clearly state all pertipent details, and give pertinent dates, including estimated date of starting an proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and some pertinent dates.									
		Shoot circu retai circu 1.65 POH. Compl	3.5" lation: ner @ 6 lation: CUFT/sx WOC. eted (p	around liner to 514' KB. Estab Mix 150 sxs o Displace w/ erations: 7/29	les @ 6636'KB. p @ 4656' KB. lish an inject f 10-1 thixact 20 BBL water. 1/85	B in 4½" liner. RIH w. POH. RIH w/ TBG/CMI ction rate 1½ BPM @ 15 d Western CMI mixed @ Good circulation the B according to CMT bords leak off.	retaind O psi to 14.0 PPo roughou	er. Set b break G and t job.		
	IICHED J	ly that the	all	is true and correct		rator Representative	065.	N (%) 2 7/31/	/85	
	•	•								
	PPROVED I		OVAL, IF	ANY:	TITLE			ACCEPTED F		

*See Instructions on Reverse Side

1985