

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NOV 2001

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

NOEL REYNOLDS D/B/A TORRED OIL COMPANY

3. Address and Telephone No.

1316 JUNIPER LANE, FORT WORTH, TX 76126

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1810' FSL, 1620' FEL
SEC. 21, T18N, R3W

5. Lease Designation and Serial No.

SF081160F

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

SAN LUIS FEDERAL #18

9. API Well No.

20812
3004320425

10. Field and Pool, or Exploratory Area

SAN LUIS MESA LEASE

11. County or Parish, State

SANDOVAL, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

AFMSS

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

Adjud *Amg*
Engr
Geol
Suri
Appr *Amg*

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 625' SURFACE CASING 7", 23#, TO 30.6'. PRODUCTION STRING 2-7/8", 7#
TUBING TO 625'. 31' BOTTOM (SLOTTED) JOINT WITH CEMENT MASKE
ON TOP, NO CEMENT ON PRODUCTION STRING.

PLUG WELL:

OPTION 1: ATTEMPT TO ESTABLISH CIRCULATION TO SURFACE BY PUMPING
CEMENT TO SURFACE FILLING INSIDE AND OUTSIDE.

OPTION 2: FILL 2-7/8" TUBING TO SURFACE WITH TRUHMIE FOR CONTROL,
AND USE CEMENT WEIGHT TO PRESSURE AVAILABLE BACKFILL.

SET DRY HOLE MARKER, POLICE LOCATION, REQUEST FINAL INSPECTION.
(OPTION SELECTION TO BE MADE BY THE OPERATOR WITH CONCURRENCE
OF BLM, BASED UPON CONDITIONS AT THE TIME.)

14. I hereby certify that the foregoing is true and correct

Signed

Noel Reynolds

Title

OPERATOR

Date

11-14-01

(This space for Federal or State office use)

Approved by

Patricia M. Hester

Title

Date

11-19-01

Conditions of approval, if any:

Plug by 12-31-2001 - Surface restoration attached