

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ WELL ☐ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Shogoil Ltd.

3. ADDRESS OF OPERATOR

P.O. Box 229, Hygiene, CO 80533

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

965' FSL and 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, or ST)

7222' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 62577

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chijiulla 31-14

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Wildcat Rio Puerco Monies

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 31, T21N, R2W

12. COUNTY OR PARISH

Sandoval

13. STATE  
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Spud & Casing Reports

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5-11-90 Spudded 12 1/4" hole at 1:45pm 5-11-90. Ran 5 jts, 210.03, to 9 5/8", 36#, J-55 casing and set at 223'. Cemented with 200sks (236 ft<sup>3</sup>) of cl B cement with 2% CaCl<sub>2</sub> and 1/4# gel-flake/sk. Circ. 48sks cement to surface. Plug down 8:30pm. Good circulation thru-out job.

5-19-90 Drilled 8 3/4" Hole to 4539'. Ran 107 jts, 4539.45', of 7", 23#, J-55 and N-80, LT&C new casing and set at 4536'. Cemented in 2 stages. First stage used 175 sks (298 ft<sup>3</sup>) of Pacesetter Lite cem. w/ 1/4# gel-flake/sk followed by 155 sks (223 ft<sup>3</sup>) of 50:50 Poz cem w/ 2% gel and 1/4# gel-flake/sk. Plug down 12:45pm. No circulation thru-out job-opened stage tool at 2190'. Well circulating. Circulated 2hrs then cemented second stage with 195 sks (449 ft<sup>3</sup>) 65:35 Poz cem. w/ 12% gel & 1/4# gel-flake/sk. Followed by 50 sks(59 ft<sup>3</sup>)cl B cem. Plug down at 4:45pm lost circulation on last 20bbbls of displacement.

5-20-90 Ran temperature survey. Top of cement at 800'.

5-22-90 Drilled 6 1/4" hole to 5673'. Ran 42 jts, 1369.49', of 4 1/2", 11.6#, K-55, ST&C new casing as liner and set at 5672' with top at 4303'. Cemented w/ 155 sks 50:50 Poz cement w/ 2% gel. Plug down at 8:00am. Circulated 20 sks off top of liner.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

5-29-90

(This space for Federal or State office use)

AREA MANAGER

RIO PUERCO RESOURCE AREA

APPROVED BY

TITLE

DATE

MAY 31 1990

CONDITIONS OF APPROVAL, IF ANY:

OPERATOR

\*See Instructions on Reverse Side

OFFICE OF THE  
DIRECTOR  
OF THE  
BUREAU OF  
INVESTIGATION  
U. S. DEPARTMENT OF JUSTICE  
WASHINGTON, D. C. 20535