

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
NMMN62577
6. If Indian, Allottee or Tribe Name
30-043-20840
7. If Unit or CA, Agreement Designation

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other
2. Name of Operator
Shogoil Ltd.

RECEIVED
NOV 23 1998
OIL CON. DIV.
DIST. 3
505-447-4734

3. Address and Telephone No.
P.O. Box 29450, Santa Fe, NM 87592-9450
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
965' PSL & 1980' FWL Sec. 31, T21N, R2W

8. Well Name and No.
Chuijuilla 3114#1
9. API Well No.
10. Field and Pool, or Exploratory Area
Rio Puerco
11. County or Parish, State
Sandoval County,
New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION
☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION
☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☒ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water
(Note: Report results of multiple completion or Completion or Recompletion Report and Log)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)
There is a use for the uncemented 7" intermediate csg. that can be recovered, so operator plans to plug and abandon the well as follows:
(1) Set a CIBP @ 4700', 58' above the BP;
(2) Dump 50' of cmt. on top of the BP;
(3) Place a plug from 2416-2516' inside the cmt. 7" int. csg., which is 50' above and below the top of the Cliffhouse Fm.;
(4) Place a plug from 1432-1582' inside the cmt. 7" int. csg., which is 50' above and below the top of the Fruitland Fm. and 50' below the top of the Pictured Cliffs Fm.;
(5) Place a plug from 1157 to 1257' inside the cmt. 7" int. csg., which is 50' above and below the top of the Ojo Alamo Fm.;
(6) Cutoff and pull 750' of 7" intermediate csg.;
(7) Set a plug from 850' (100' inside the 7" csg.) to 650' (100' into the 8 3/4" hole);
(8) Plug from 273' (50' below the base of the 9 5/8" csg.) to the surface using 130 sx. of cmt.;
(9) Install a marker and reseed and restore the well pad and access as specified in the APD.

4. I hereby certify that the foregoing is true and correct
Signed John B. Ames II
(This space for Federal or State office use)
Approved by [Signature]
Conditions of approval, if any:

Title Petroleum Engineer Date Oct. 1
Lands and Mineral Resources NOV
Title _____ Date _____