

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well:

Oil ☐ Gas ☐
Well ☒ Well ☒ Other ☐

2. Name of Operator:

Energy Development Corporation

3. ADDRESS OF OPERATOR

1000 Louisiana, Ste. 2900, Houston, TX 77002

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1150' FSL & 1620' FEL, Section 5-T20N-R2W

FORM APPROVED

BUDGET BUREAU NO. 1004-0135

EXPIRES MARCH 31, 1993

5. Lease Designation and Serial No.
NM-84664

6. If Indian, Allocate or Tribe Name
NA

7. If Unit or CA, Agreement Designation
San Isidro (Shallow)

8. Well Name and No.
San Isidro No. 5-15

9. API Well No.
30-043-20923

10. Field and Pool, or Exploratory Area
Rio Puerco - Mancos Pool

11. County or Parish, State
Sandoval County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____

☐ Change of Plans
☒ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report result on multiple completion on Well Completion or Recompletion Report Log form).

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location and measured and true vertical depths for all markers and zones pertinent to this work).

Drilled 6-3/4" hole to 4925', due to continued shows at originally permitted TD to test the *Semilla*. 11-9-94: Ran & set 5-1/2", 17#/ft, N-80, LTC production casing to 4910' with float shoe, 2 float joints, and float collar. Cemented w/190 sxs Class "B" cement + .4% CFR-3 + .4% Halid 344 with 1.18 ft³/sx yield at 15.6 ppg slurry density. Top of cement at 3220' by CBL. Tested casing to 1000 psig. Four Corner rig off location at 1300 hours on 11-9-94.

14. I hereby certify that the foregoing is true and correct

Signed Paul E. Schwinn Title Reg. & Environ. Affairs Engineer Date 1-19-95

(This space for Federal or State Office use)

Approved by [Signature] Title for Chief, Lands and Mineral Resources Date JAN 20 1995

Approval to NMADN (Dorothy) per fax 1/20/95