

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency

Allottee

Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 20, 1954

Well No. 2 is located 423 ft. from S line and 2000 ft. from W line of sec. 36

24 Sec. and Sec. No. 24-25 13-27 New Mexico P.M.
(Twp.) (Range) (Meridian)
Willard New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ground above sea level is 2000 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mud logging jobs, logging points, and all other important proposed work)

9.20. 1954

September 9, 1954

Well planned and described as follows:

200' to 250' - 2 1/2" - 20 lb. cement plug.
250' to 275' - 2 1/2" - 20 lb. cement plug.
275' to 300' - 2 1/2" - 20 lb. cement plug.
300' to 325' - 2 1/2" - 20 lb. cement plug.
325' to 350' - 2 1/2" - 20 lb. cement plug.
350' to 375' - 2 1/2" - 20 lb. cement plug.
375' to 400' - 2 1/2" - 20 lb. cement plug.
Bottom plug (Top of 4-5/8" casing) - 5 lb. cement plug.
Heavy drilling and between cement plugs.

Well surface installed according to regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Perm Oil Company

Address P. O. Box 207

Willard, New Mexico

By

Title Production Chief

