

5 U.S.G.S. Farmington

1 Robert Ramirez

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other: _____)
(Indicate on reverse side)

Form approved
Bureau of Reclamation No. 42-813

3. LEASE DESIGNATION AND STATE NO.

NM-5454

6. IF INDIAN, RESERVE OR TRUST NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal F

9. WELL NO.

1

10. FIELD AND TOWN OF WILDCAT

Nageezi Gallup

11. SEC., T., R. OR BLK. AND
SURFACE OR AREA

8-23N-8W NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different well.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

BCO, Inc.

3. ADDRESS OF OPERATOR

135 Grant Ave. Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1960' FEL 2080' FSL Sec 8 T23N R8W NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, AT, CT, etc.)

GR 6857

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☒

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and pertinent to this work.)

Believe well has casing failure, Intend to set RBP above Gallup perfs (5068-5210) and then use a packer to find the hole in the casing. Intend to repair said hole with cement, let cement set for at least 72 hours, then drill out the cement, remove RBP, swab well and place back in production.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. Barnes

TITLE

Office Manager

DATE

3/24/83

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

NMOCC

DATE