

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0555915

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Fenby

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

9-T23N-R13W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5936 GR

12. COUNTY OR PARISH

San Juan

13. STATE

N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well was drilled to TD at 9803' on 1/20/72 & decision was made to P & A according to the following procedure requested by the USGS, Farmington, New Mexico:

- 1) 100 sack cement plug 9803-9640
- 2) 60 sack cement plug 9100-8900
- 3) 60 sack cement plug 7300-7100
- 4) 45 sack cement plug 5800-5650
- 5) 45 sack cement plug 5350-5200
- 6) 90 sack cement plug 4930-4630
- 7) Rig up casing pulling contractor and pull approx. 3000' of 8 5/8" intermediate
- 8) Place 100 ft. plug in & out of 8 5/8" csg. stub.
- 9) 45 sack cement plug 2300-2650
- 10) Place 100 ft. plug in & out of 13 3/8" CD surface casing
- 11) 25 sack cement plug in top of 13 3/8" w/ DH marker

Note: If no 8 5/8" csg. is recovered, casing will be perforated at the listed intervals and squeeze cemented. Bedford, Inc., P. O. Box 2, Farmington, New Mexico will be the plugging contractor, following items 7-11 outlined in accordance with USGS requirements.

18. I hereby certify that the foregoing is true and correct

SIGNED

Raymond A. Somers

TITLE **Regional Production Manager**

DATE **2-3-72**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
FEB 7 1972

U.S. GEOLOGICAL SURVEY

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.