Form 9-331 (May 1963)

## UNITED STATES SUBMIT IN TRIPLICATE\* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

San Juan

New Mexico

GEOLOGICAL SURVEY	NM-19572 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	O. IF INDIAN, ALLOTTEE OR TRIBE NAME	
OIL GAS WELL OTHER	7. UNIT AGREEMENT NAME	
Tesoro Petroleum Corporation	8. FARM OR LEASE NAME  McKnight Federal  9. WELL NO.	
3. ADDRESS OF OPERATOR 633 17th Street, Suite 2000, Denver, Colorado 82025 1.	1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State regulariests.) See also space 17 below.) At surface  790' FSL and 790' FWL (SW/4; SW/4;	Wildcat  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
14. PERMIT NO.   15. ELEVATIONS (Show whether DF, RT, GR, etc.)	Sec. 24, T23N, R13W	

		<u> </u>		
6.	Check Appropriate Box	To Indicate Nature	of Notice, Repo	ort, or Other Data

5977 GI

NOTIC	E OF INTENTION TO:	SUBSEQUENT REPOR	T OF:	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	water shut-off  FRACTURE TREATMENT  SHOOTING OR ACIDIZING  (Other) Spudding Well  (Note: Report results of multip Completion or Recompletion Report	REPAIRING WELL  ALTERING CASING  ABANDONMENT*	
(Other)		Completion or Recompletion Repo	rt and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Tesoro Petroleum Corporation operations on the above captioned well are as follows:

3/1/75 Spudded 12½" hole at 9:00 a.m. 2/28/75. Drilling at 120' this a.m.

3/2/75 Drilled to 187'. Ran 8 5/8", 20# , H-40 casing to 187' and cemented with 200 sacks of Class "A" cement + 2% CaCl. Cement circulated to surface.

U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct	TITLE	District Engineer	<sub>DATE</sub> 3/19/75
(This space for Federal or State office use)  APPROVED BY	TITLE		DATE