

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other WILDCAT

2. NAME OF OPERATOR
SAN JUAN VENTURE

3. ADDRESS OF OPERATOR OKLAHOMA CITY, OK
6207 NW EXPRESSWAY 73132

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790' FSL, 1850' FEL SEC 22

AT TOP PROD. INTERVAL: SAME

AT TOTAL DEPTH: ✓

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) RE-ENTER

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE NM

FENNER 13609

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

MIDWAY

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

NONE MIDWAY

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 22-T 22N-R 8W

12. COUNTY OR PARISH | 13. STATE

SAN JUAN

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

KB 6630, GR 6643

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RE-ENTER 11-20-77, DRILL OUT CEMENT PLUGS TO APPROX 1450 (OLD TO 1463)
RUN 4 1/2" CSC, PERF 1397-79 & 1400-83 CHACRA, ACID 250 GAL MCA, FRAC 10,000-
10,000, IF COMMERCIAL COMPLETE USING 2 3/8" TUBING. IF NON-COMMERCIAL LIGHT
SQUEEZE, PERF, ACID & FRAC 1204-66, 1270-72 & 1276-79 LA VENTANA. IF NON-
COMMERCIAL, LIGHT SQUEEZE, PERF, ACID & FRAC 1163-66, 1174-77, 1183-86
LA VENTANA. POSS ABOVE PROCEDURE 1066-69, 1075-78, 1089-92 LA VENTANA
§ 698-706 PICTURED CLIFFS

EST TOP/CRETACEOUS 167'

FRUITLAND 498'

PICTURED CLIFFS 690'

LEWIS 890'

LA VENTANA

1052'

CHACRA

1353'

TO CHACRA

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Warren E. Carr TITLE Participant

DATE

11-19-77

(This space for Federal or State office use)


APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

from George E. Coleman



*See Instructions on Reverse Side

RECEIVED

NOV 21 1977

U.S. Geological Survey
Farmingington, N.M.