

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL 1850' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE

NM-13609

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Midway

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 22, T22N R8W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6641' gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JUL 6 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Verbal approval obtained from Mr. Richard Bell on 6/22/82 to P&A as follows:

6/22/82 - MIRUSU. NUBOP. RIH w/tbg. Tagged btm at 1354'. POOH. Perf'd four squeeze holes at 450' and four squeeze holes at 90'. RIH w/cmt retainer and set at 400'. Cemented w/100 sx C1-B neat cmt using enough excess to include 100' cmt plug from 450-350 in 6-1/4" hole - 4-1/2" csg annulus. Stung out of retainer. Pulled out of hole w/tbg while spotting 24 sx cmt from 400' to squeeze holes at 90'. Finished pulling out of hole and pmpd 16 sx cmt dn 4-1/2 to fill remainder of csg and spot cmt plug fr 90' to surface in annulus. Cmt to surface. RDMOSU.

6/23/82 - CU location and install dry hole marker.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Denise Wilson

TITLE Production Analyst

DATE 6/30/82

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APR 10 1984

*See Instructions on Reverse Side

NMOCC