

API NUMBER	30-045-23027	SUR CSG OD	9.68	cmt	cmt	cmt	cmt
OPERATOR NAME	APA Develop Corp.	SUR CSG TD	183	cmt	cmt	cmt	cmt
PROPERTY NAME	Santa Fe Leggs	SURF CSG WT	32.3	cmt	cmt	cmt	cmt
WELL NUMBER	2	TOP OF CMT	0	cmt	cmt	cmt	cmt
SECTION	11	ACTUAL	CIRC	cmt	cmt	cmt	cmt
TOWNSHIP	21N	CACULATED		cmt	cmt	cmt	cmt
RANGE	10W			cmt	cmt	cmt	cmt
FOOTAGE	990' FSL 2310' FWL			cmt	cmt	cmt	cmt
BOND # 246					cmt	cmt	
FORMATION, TOP	TOPS TO ISOLATE	PROD CSG OD	7		cmt	cmt	
entrada	5415	PROD CSG TD	5584		cmt	cmt	
Todilto	5401	PROD CSG WT	20&		cmt	cmt	
Morrison	4487	TOP OF CMT	0		cmt	cmt	
dakota	4302	ACTUAL	CIRC		cmt	cmt	
greenhorn	4120	CACULATED			cmt	cmt	
Gallup	2980	DV Tool	2824		cmt	cmt	
mancos	2270	PACKER			cmt	cmt	
point lookout	2196				cmt	cmt	
		PERF TOP	5415		cmt	cmt	
		PERF BOTTOM	5422		cmt	cmt	

TYPE OF PLUG	PLUG SET AT	OPEN HOLE
---------------------	--------------------	------------------

PROPOSED PLUGGING OPERATION

Move in, Rig up Well Service Unit, Nipple down well head, Nipple up BOPE

PICK UP WORK STRING

PLUG @ 5400-5100 TAG PLUG, TEST CSG, IF CSG DOES NOT TEST,
TAG PLUGS AS REQUIRED

PLUG @ 4570-4150'

PLUG @ 3005-2855'

PLUG @ 1200-1050'

PLUG @ 270' TO SURFACE

INSTALL P&A MARKER

CLOSE PITS ACCORDING TO NMOCD GUIDELINES

CLEAN AND LEVEL LOCATION