

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 6683

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 21-23-8

9. WELL NO.

No. 1

10. FIELD AND POOL, OR WILDCAT

Wildcat *Chaco*11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 21-T23N-R8W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Benson Mineral Group, Inc.

3. ADDRESS OF OPERATOR

1726 Champa St., Suite 600, Denver, CO 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1460' FWL & 970' FSL, Section 21-T23N-R8W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6816' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT* ☒

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Benson Mineral Group, Inc. plugged and abandoned the above location with 56 sx class B cement from 1834' to 1109', followed by a 4 1/2" wiper plug, 12 bbls of 9#/gal mud, 8 sx class B cement from 400' to 300', 4 bbls of 9#/gal mud, and 4 sx class B cement from 50' to surface. A P & A marker was erected, and the location was cleaned. Re-seeding will take place July 1, 1980 as per USGS requirements.

APR 7 1984
OIL & GAS DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Paul C. Ellison
Paul C. Ellison

TITLE

Vice President

DATE

June 11, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side