

SUPPLEMENTAL INFORMATION TO FORM 9-331C
REQUIRED BY NTL-6

FEDERAL 35-23-8 Well #1
800FSL & 1500FEL Sec. 35-T23N-R8W
San Juan County, New Mexico

The geologic name of the surface formation is: Tertiary Nacimiento

The estimated tops of important geological formations bearing hydrocarbons to be drilled are:

<u>Formation</u>	<u>Depth</u>	<u>Elevation</u>
Chacra	1689	+5200
Total Depth	1850	

Estimated K.B. elevation: 6889 GR.

<u>Estimated Depth</u>	<u>Casing Size</u>	<u>Casing Weight</u>	<u>Hole Size</u>	<u>Sacks Cement</u>	<u>Type</u>
100	7" Used	23	9 5/8"	50	Class "B" 2% CaCl ₂
1850	4 1/2" New	9.5	6 1/2"	50 150	Class "B" Class "B" 50-50 Poz mix, 6% gel with 1/2# Celloflake/sack

Benson Mineral Group Inc.'s standard blowout prevention will be employed, see the attached drawing of the preventor design.

Drilling fluid to be a low solids non-dispersed mud system.

The logging program will be as follows: Induction-Electric and Compensated Density-Gamma Ray from surface casing point to total depth.

Past experience in this area has shown that no abnormal pressures, temperatures, or hydrogen sulfide gas will be encountered.