

API NUMBER	30-045-23227	SUR CSG OD	9.68	cmt	cmt	cmt	cmt
OPERATOR NAME	APA Develop Corp.	SUR CSG TD	185	cmt	cmt	cmt	cmt
PROPERTY NAME	Santa Fe Barbs	SURF CSG WT	32.3	cmt	cmt	cmt	cmt
WELL NUMBER	1	TOP OF CMT	0	cmt	cmt	cmt	cmt
SECTION	10	ACTUAL	CIRC	cmt	cmt	cmt	cmt
TOWNSHIP	21N	CACULATED		cmt	cmt	cmt	cmt
RANGE	10W			cmt	cmt	cmt	cmt
FOOTAGE	990' FSL 500' FWL			cmt	cmt	cmt	cmt
BOND # 238				cmt	cmt	cmt	cmt
FORMATION, TOP	TOPS TO ISOLATE	PROD CSG OD	7	cmt	cmt	cmt	cmt
entrada	5424	PROD CSG TD	5607	cmt	cmt	cmt	cmt
Todilto	5416	PROD CSG WT	20&	cmt	cmt	cmt	cmt
Morrison	4506	TOP OF CMT	0	cmt	cmt	cmt	cmt
dakota	4322	ACTUAL	CIRC	cmt	cmt	cmt	cmt
greenhorn	4143	CACULATED		cmt	cmt	cmt	cmt
Gallup	3000	DV Tool	3876	cmt	cmt	cmt	cmt
mancos	2294	PACKER		cmt	cmt	cmt	cmt
point lookout	2202			cmt	cmt	cmt	cmt
		PERF TOP	3316	cmt	cmt	cmt	cmt
		PERF BOTTOM	3334	cmt	cmt	cmt	cmt
		perf also 5516-5595					
TYPE OF PLUG	PLUG SET AT	OPEN HOLE					

PROPOSED PLUGGING OPERATION

Move in, Rig up Well Service Unit, Nipple down well head, Nipple up BOPE

PICK UP WORK STRING

PLUG @ 5500-5145' TAG PLUG

PLUG @ 4615-4195' TAG PLUG

PLUG @ 3300-3150' TAG PLUG, TEST CASING, IF CASING DOES NOT TEST,
TAG PLUGS AS REQUIRED

PLUG @ 3050-2900'

PLUG @ 1245-1095

PLUG @ 260 TO SURFACE

INSTALL P&A MARKER

CLOSE PITS ACCORDING TO NMOCD GUIDELINES

CLEAN AND LEVEL LOCATION