

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-8904

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Beard Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat Chacra

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

5-T 22N-R 8W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. OIL ☐ WELL GAS ☒ WELL OTHER ☐

2. NAME OF OPERATOR

Davis Oil Company

3. ADDRESS OF OPERATOR

1424 Tenth Street, Rock Springs, Wyoming 82901

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

SE-SW Sec. 5 T22N R8W

1000' FSL 1640' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6797 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Total Depth - 1741'

Last Production - well has not been produced.

Casing - 90' 8 5/8" 24# K-55 STC Cement to surface 1741' 4 1/2" 10.5# K-55 LTC  
175 sxs (Cement in hole 375' - 1741')

Perfs - 1345' - 1440' 34 holes Upper Chacra Fm.

Cast Iron Bridge Plug @ 480' w/1 sack cement on top

Squeeze @ 270' 3 squeezes - total cement 195 sxs cement in hole 200' - 375'

Perfs - 300' - 324'; 336' - 355' 1 SPF Oja Alamo Fm

No show of gas, oil or water.

Plugging Procedure:

Fill 4 1/2" casing w/cement from CIBP (480') to surface w/approximately 38 sxs

Pressure to 500 psi - 1000 psi at perfs

Cut off casing head

Set regulation dry hole marker

Recontour location per B.L.M. stipulations.

Set cement plug from 700' to 1300' and  
tag top of cement (if a bridge plug is  
set at 1300' the requirement to tag  
cement top will be waived)

18. I hereby certify that the foregoing is true and correct

SIGNED *BL Santos*

TITLE District Superintendent

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

\*See Instructions on Reverse Side

