

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 155' FNL & 1115' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

5. OTHER DATA TO INDICATE NATURE OF WELL, SUCH AS
WELL OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT OFF

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

WATER TREAT

5. LEASE

NM-19569

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Tsaya

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Wildcat *Cakota*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 4, T22N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO

15. ELEVATIONS (SHOW OF HOB AND WS.)
8170' GR

RECEIVED

NOV 26 1984

OIL CON. DIV.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-31-80 Spotted plugs as follows:

Plug #1 from 4720' to 4266' cemented with 130 sacks of Class "B".

Plug #2 from 3620' to 3420' cemented with 75 sacks of Class "B".

Plug #3 from 2650' to 2446' cemented with 85 sacks of Class "B".

Plug #4 from 530' to 310' cemented with 70 sacks of Class "B".

Plug #5 from 36' to 3' cemented with 10 sacks of Class "B".

Installed dry hole marker.

Location cleanup will be at a later date.

10-29-80 VERBAL APPROVAL FROM BRUCE WAMSBY, USGS, TO JOHN CRUM, SOUTHLAND ROYALTY COMPANY.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]* TITLE District Engineer DATE November 1, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

NMOCC

*See Instructions on Reverse Side

M. MILLENBACH
AREA MANAGER