Form Approved.

Form 9-331 Dec. 1973

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Form 9-331	Budget Bureau No. 42-K1424	
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE NM 8902	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Billie	
1. oil gas well other	9. WELL NO. #3	
2. NAME OF OPERATOR Dugan Production Corp.	10. FIELD OR WILDCAT NAME Wildcat	
3. ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec 4 T21N R8W	
below.) at surface: 1550' FNL - 1850' FWL at top prod. Interval:	12. COUNTY OR PARISH 13. STATE San Juan NM	
AT TOTAL DEPTH:	14. API NO.	

AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD) 6785' GR

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

SUBSEQUENT REPORT OF: (NOTE: Report results of multiple,

change on Form 9-830.) F casting - CORRECTION

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Cement for

Per your instructions, the following is a **CORRECTED REPORT** REPLACING INFORMATION SUBMITTED 2-19-81:

Rigged up and ran 58 jts. 2-7/8" OD, 6.4#, 10 Rd NEUE tbg. for 2-15-81 csg. T.E. 1437.74' set at 1436' GL. Cemented with 75 sx 2% Lodense w/ ¼# cello flake per sx followed by 50 sx class B with ¼# cello flake per sx. Total slurry 211 cu.ft.

> Reciprocated pipe OK while cementing. Good circulation throughout job. P.O.B. at 1:30 p.m. 2-14-81. (Circulated trace of cement to surface.)

and Type		Set @ Ft.
Subsurface Safety Valve: Manual and Type		
18. I hereby certify that the lovegoing is	true and correct TITLE Petroleum Enginee BATE 2- (This space for Federal or State office use)	12-82
SIGNED Thomas A. Duran	(This space for Federal or State office use)	ACCENTED CO. CT.
V		ACCEPTED FOR RECORD
APPROVED BY	TITLE DATE	FEB 1 6 1982

NMOCC

BY SO FARMINGIUM DISTHICT