ONITED S	IAIL	.5
DEPARTMENT OF	THE	INTERIOR
GEOLOGICAL	SUR	VEY

VAUNIS	NOTICES	AND	REPORTS	ON	WELLC
JUNDKI	MOLICES	ANU	REPURIS	UN	WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1.	oil well		gas well		other	Dry	Hole	
2.	NAM	E OF	OPERA	TOR		1		
	Rir	o b	il Co	orpo	oration	v		

3. ADDRESS OF OPERATOR

Denver, 717 17th St., Ste. 2860 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 2110' FNL & 990' FEL (SENE)

AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

	J. LEASE						
	NOO-C-14-20-5818						
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME						
-	Pah						
	7. UNIT AGREEMENT NAME						
ĺ							
	8. FARM OR LEASE NAME						
	Bird-Pah						
	9. WELL NO.						
1	#10-1						
	10. FIELD OR WILDCAT NAME						
	Wildcat /						
	11. SEC., T., R., M., OR BLK. AND SURVEY O						
I	AREA						
ı	Sec.10-T22N-R9W						
I	12. COUNTY OR PARISH 13. STATE						
۱	San Juan New Mexico						
l	14. API NO.						
I							
١	15. ELEVATIONS (SHOW DF, KDB, AND WD						
ĺ	6504' GL, 6517' KB						

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON* (other)

SUBSEQUENT REPORT OF: (NOTE U. S. GEOLOGICAL SURVEY

FARMINGTON, N. M.

Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Subject well has been PxA'd as of Jan. 5, 1982 as follows:

80202

Plug	Sxs	Depth	<u>Formation</u>
1	25	6050-6150'	Top of Entrada (6100')
2	25	3810-3910'	Bot of Gallup (3860')
3	25	3040-3140'	Bot of Pt Lookout (3090')
4	25	1455-1555'	Top of Menefee (1505')
5	25	330-430'	Bot of 9 5/8" Surface (387')
6	5	Surface	avea to A WEM

Subsurface Safety Valve: Manu. and Type

Set @ .

the for egoing is true and correct

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

(This space for Federal or State office tise) TITLE

DATE APPROVED

Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.

See Instructions on Reverse Side

FARMINGTON COPY

MANAGER