STATE OF NEW MEXICO ENERGY 410 MINERALS DEPARTMENT

-0, 07 (0*160 *(661460	T	
DISTRIBUTION		
SANTA FE	Ī	i .
FILE	1	
U.S.G.S.		
LAND OFFICE	1	
OPERATOR	1	

-0. 07 (0-160 *(((1)*(0	OIL CONSERVATION DIVIS	NON
DISTRIBUTION	P. O. BOX 2088	Form C-103
SANTA FE		
FILE	SANTA FE, NEW MEXICO 8750	01
U.S.C.S.	•	Sa. Indicate Type of Lease
LAND OFFICE		State X
OPERATOR	•	5. State Oil & Gas Lease No.
		LH-1896
SUNDRY	NOTICES AND REPORTS ON WELLS	
OIL X CAS WELL	OTHER-	7. Unit Agreement Name
Name of Operator		8. Fam or Lease Ivane
DUGAN PRODUCTION CORP.		1541- 5-4
Address of Operator		Wit's End
P O Box 208, Farmingto	on, NM 87499	3
ocation of Well		10. Field and Pool, or Wildcat
UNIT LETTER K 1500	PEET FROM THE South LINE AND 1980	Undesignated Gallup
	2 TOWNSHIP 23N RANGE 10	
	15. Elevation (Show whether DF, RT, GR, etc.) 6740' GL; 6752' RKB	12. County San Juan
Check App	propriate Box To Indicate Nature of Notice,	Report of Other Data
NOTICE OF INTE	ENTION TO:	SUBSEQUENT REPORT OF:
FORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING

Reached T.D. of 4898' on 5-27-85.

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, inc

OIL CON. DIV. DIST. 3

MAY 2 9 1985

casing & cement

Laid down drill pipe and collars and ran 116 joints of $4\frac{1}{2}$ " OD, 10.5#, J-55, 8 Rd, ST&C casing (T.E. 4890.20') set at 4898' RKB. Cement 1st stage with 10 bbls mud flush and 200 sx 50/50 poz with 2% gel and $\frac{1}{4}$ # flocele per sack (total slurry 254 cf). Had good circulation and reciprocated pipe while cementing. Bump plug with 1000 psi - held OK. P.O.B. at 11:50 PM 5-27-85. Open DV tool with 1000 psi. Circulate 3 hrs with rig pump. Cement 2nd stage with 10 bbls mud flush and 440 sacks 65/35 + 12% gel + $\frac{1}{4}$ # flocele per sack, followed by 120 sacks 50/50 poz with 2% gel + $\frac{1}{4}$ # flocele per sack (total slurry 1125 cf). Good circulation while cementing. Circulated 2 bbls cement to surface. - Bump plug with 2400 psi - held OK. P.O.B. at 3:30 AM on 5-28-85. Set slips and released rig at 5:00 AM on 5-28-85. (Note: Total cement slurry used in both stages = 1379 cf).

18. I hereby certify that the information above is true and cor	npiete to the bes	t of my knowledge and belief.	
Jim L. Jacobs	* ! 7 E	Geologist	5-28-85
		•	a 0 100F
Driginal Signed by FRANK T. CHAVEZ		SUPERVISOR DISTRICT # 3	MAY 29 19 85

work) SEE RULE 1103.