

5 BLM 1 Celsius-Denver 1 Celsius-SLC 1 BIA  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 10040935  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.  
N00-C-14-20-7308

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Marathon

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undes. Gallup

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec.4, T23N, R10W, NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR  
DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

630' FNL - 550' FEL

RECEIVED

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

6660' GL; 6672' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & Surface Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in and rigged up Four Corners Drilling Company rig #3.  
Spudded 12 1/4" hole at 10:30 AM 9-18-85. Drilled to 235'.  
Ran 8 jts. 8-5/8" OD, 24#, J-55, 8 Rd, ST&C casing (T.E.  
214') set at 226' RKB. Cemented with 135 sacks (159 cf) of  
class "B" + 2% CaCl<sub>2</sub>. P.O.B. at 3:00 PM 9-18-85. (Circulated  
approx. 1 1/2 bbls cement). Pressure tested BOP and surface casing  
600 psi for 30 minutes - held OK.

RECEIVED  
SEP 25 1985  
OIL COM. DIV.  
DIST. 6

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE Geologist

DATE 9-19-85  
ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE 9-21-85

FARMINGTON RESOURCE AREA

\*See Instructions on Reverse Side

BY  
NMOCC